

3
4
5
6 Internet Printing Protocol (IPP): Production Printing Attributes - Set1
7 <pwg-ipp-prod-print-set1-000605.rtf, .pdf>
8

9 Status of this Memo

10
11 This document is a draft of an IEEE-ISTO PWG Proposed Standard and is in full conformance with all
12 provisions of the PWG Process (see <http://www.pwg.org/chair/pwg-process-990825.pdf>). PWG Proposed
13 Standards are working documents of the IEEE-ISTO PWG and its working groups.
14

15 The list of current PWG drafts can be obtained at <http://www.pwg.org/pub/pwg/ipp>
16
17

18 Abstract
19

20 This document specifies an extension to the Internet Printing Protocol/1.0 (IPP) [RFC2565, RFC2566] and
21 IPP/1.1 [ipp-mod, ipp-pro]. This extension consists primarily of Job Template attributes defined for
22 submitting print jobs to production printers. These attributes permit a user to control and/or override
23 instructions in the document content to perform the following functions: print on document covers, insert
24 sheets into the document, provide an accounting id, request accounting sheets, provide job sheet messages,
25 request error sheets, provide a message to the operator, provide a job recipient name in cases that is
26 intended to be different from the job submitter's name, control the media used for job sheets, request media
27 by characteristic (size, weight, etc.), control collation, and shift the image.
28

29 This extension also defines the "current-page-order" Job Description attribute, the "user-defined-names-
30 supported" Printer Description attribute, and the 'resources-are-not-supported' value for the "job-state-
31 reasons" Job Description attribute.
32

33 Some additional "media" keyword values are defined for use with the "media" Job Template attribute.

34 The full set of IPP documents includes:

35

36 Design Goals for an Internet Printing Protocol [RFC2567]

37 Rationale for the Structure and Model and Protocol for the Internet Printing Protocol [RFC2568]

38 Internet Printing Protocol/1.1: Model and Semantics (this document)

39 Internet Printing Protocol/1.1: Encoding and Transport [IPP-PRO]

40 Internet Printing Protocol/1.1: Implementer's Guide [IPP-IIG]

41 Mapping between LPD and IPP Protocols [RFC2569]

42

43 The "Design Goals for an Internet Printing Protocol" document takes a broad look at distributed printing
44 functionality, and it enumerates real-life scenarios that help to clarify the features that need to be included
45 in a printing protocol for the Internet. It identifies requirements for three types of users: end users,
46 operators, and administrators. It calls out a subset of end user requirements that are satisfied in IPP/1.0. A
47 few OPTIONAL operator operations have been added to IPP/1.1.

48

49 The "Rationale for the Structure and Model and Protocol for the Internet Printing Protocol" document
50 describes IPP from a high level view, defines a roadmap for the various documents that form the suite of
51 IPP specification documents, and gives background and rationale for the IETF working group's major
52 decisions.

53

54 The "Internet Printing Protocol/1.1: Encoding and Transport" document is a formal mapping of the abstract
55 operations and attributes defined in the model document onto HTTP/1.1 [RFC2616]. It defines the
56 encoding rules for a new Internet MIME media type called "application/ipp". This document also defines
57 the rules for transporting over HTTP a message body whose Content-Type is "application/ipp". This
58 document defines a new scheme named 'ipp' for identifying IPP printers and jobs.

59

60 The "Internet Printing Protocol/1.1: Implementer's Guide" document gives insight and advice to
61 implementers of IPP clients and IPP objects. It is intended to help them understand IPP/1.1 and some of the
62 considerations that may assist them in the design of their client and/or IPP object implementations. For
63 example, a typical order of processing requests is given, including error checking. Motivation for some of
64 the specification decisions is also included.

65

66 The "Mapping between LPD and IPP Protocols" document gives some advice to implementers of gateways
67 between IPP and LPD (Line Printer Daemon) implementations.

68

Table of Contents

69

70

71 **1 Introduction.....7**

72 **2 Terminology7**

73 2.1 Conformance Terminology..... 7

74 2.2 Other terminology.....8

75 2.3 Coordinate System.....8

76 2.4 Enumeration and Ordering of print-stream pages9

77 2.5 Collection Attributes10

78 2.6 Definition of 'none' values10

79 **3 Job Template Attributes11**

80 3.1 cover-front (collection) and cover-back (collection).....12

81 3.1.1 media (type3 keyword | name(MAX)) or media-col (collection).....13

82 3.1.2 cover-type (type2 keyword).....13

83 3.1.3 cover-front-default (collection) and cover-back-default (collection).....15

84 3.1.4 cover-front-supported (1setOf type2 keyword), cover-back-supported (1setOf type2 keyword)15

85 3.2 insert-sheet (1setOf collection).....15

86 3.2.1 insert-after-page-number (integer(0:MAX))16

87 3.2.2 insert-count (integer(0:MAX)).....16

88 3.2.3 media (type3 keyword | name(MAX)) or media-col (collection).....17

89 3.2.4 insert-sheet-default (1setOf collection).....17

90 3.2.5 insert-sheet-supported (1setOf type2 keyword)17

91 3.3 job-account-id (name (MAX)).....17

92 3.3.1 job-account-id-supported (integer(1:255)).....18

93 3.4 job-accounting-sheets (collection).....18

94 3.4.1 job-accounting-sheets-type (type3 keyword | name(MAX))18

95 3.4.2 media (type3 keyword | name(MAX)) or media-col (collection).....19

96 3.4.3 job-accounting-sheets-default (collection).....19

97 3.4.4 job-accounting-sheets-supported (1setOf type2 keyword).....19

98 3.5 job-error-sheet (collection).....20

99 3.5.1 job-error-sheet-type (type3 keyword | name(MAX)).....20

100 3.5.2 job-error-sheet-when (type2 keyword).....20

101 3.5.3 media (type3 keyword | name(MAX)) or media-col (collection).....21

102 3.5.4 job-error-sheet-default (collection)21

103 3.5.5 job-error-sheet-supported (1setOf type2 keyword)22

104 3.6 job-message-to-operator (text(MAX))22

105 3.6.1 job-message-to-operator-supported (integer(0:1023))22

106 3.7 job-recipient-name (name(MAX))22

107 3.7.1 job-recipient-name-supported (integer(0:255)).....23

108 3.8 job-sheets-col (collection) - augments IPP/1.1 "job-sheets"23

109 3.8.1 job-sheets (type3 keyword | name(MAX))23

110 3.8.2 media (type3 keyword | name(MAX)) or media-col (collection).....24

111 3.8.3 job-sheets-col-default (collection).....24

112 3.8.4 job-sheets-col-supported (1setOf type2 keyword)25

113 3.9 job-sheet-message (text(MAX)).....25

114 3.9.1 job-sheet-message-supported (integer(0:1023)).....25

115 3.10 media-col (collection) - augments IPP/1.1 "media"25

116 3.10.1 media-description (type3 keyword | name(MAX))27

117 3.10.2 media-color (type3 keyword | name(MAX)).....28

118 3.10.3 media-opacity (type3 keyword).....28

119 3.10.4 media-pre-printed (type3 keyword | name(MAX))29

120 3.10.5 media-tabs (type3 keyword).....29

121 3.10.6 media-hole-count (integer(0:MAX)).....29

122 3.10.7 media-order-count (integer(1:MAX))30

123 3.10.8 media-label-type (type3 keyword | name(MAX))30

124 3.10.9 media-size (collection)30

125 3.10.10 media-weight-metric (integer(0:MAX)).....32

126 3.10.11 media-weight-english (integer(0:MAX))32

127 3.10.12 media-front-coating (type3 keyword | name(MAX)) and media-back-coating (type3 keyword |

128 name(MAX))32

129 3.10.13 media-recycled (type3 keyword | name(MAX)).....33

130 3.10.14 media-default (type3 keyword | name(MAX)) or media-col-default (collection)33

131 3.10.15 media-ready (1setOf (type3 keyword | name(MAX))) and media-col-ready (1setOf collection)34

132 3.10.16 media-col-supported (1setOf type2 keyword).....34

133 3.11 page-delivery (type2 keyword)34

134 3.11.1 Interaction with the "page-order-received" attribute35

135 3.12 page-order-received (type2 keyword).....36

136 3.13 separator-sheets (collection)37

137 3.13.1 separator-sheet-type (type3 keyword | name(MAX))37

138 3.13.2 media (type3 keyword | name(MAX)) or media-col (collection).....38

139 3.13.3 separator-sheets-default (collection)38

140 3.13.4 separator-sheets-supported (1setOf type2 keyword)38

141 3.14 Impression Image Shifting Attributes.....39

142 3.14.1 x-image-auto-center (boolean)39

143 3.14.2 x-image-shift (integer(MIN:MAX)).....39

144 3.14.3 x-side1-image-shift (integer(MIN:MAX))40

145 3.14.4 x-side2-image-shift (integer(MIN:MAX))40

146 3.14.5 y-image-auto-center (boolean)41

147 3.14.6 y-image-shift (integer(MIN:MAX))41

148 3.14.7 y-side1-image-shift (integer(MIN:MAX))41

149 3.14.8 y-side2-image-shift (integer(MIN:MAX))42

150 3.15 Usage in Document-Exceptions and Page-Exceptions.....42

151 **4 Job Description Attributes.....44**

152 4.1 current-page-order (type2 keyword)44

153 **5 Printer Description Attributes.....44**

154 5.1 user-defined-names-supported (1setOf type2 keyword).....44

155 **6 Additional Values for Existing Attributes.....45**

156 6.1 Additional values for the "job-state-reasons" Job attribute45

157 6.2 Additional values for the IPP/1.1 "job-sheets" Job Template Attribute45

158 6.3 Additional values for the IPP/1.1 "media" and "media-description" attributes.....46

159 **7 Conformance Requirements47**

160 7.1 Conformance Requirements for Printer objects47

161 7.2 Conformance Requirements for clients48

162 **8 IANA Considerations48**

163 **9 Internationalization Considerations48**

164 **10 Security Considerations48**

165 **11 References49**

166 **12 Author's Addresses.....49**

167 **13 Appendix A: Change History50**

168 13.1 Changes to the May 9, 2000 to create the June 5, 2000 version.....50

169 13.2 Changes to the April 26, 2000 to create the May 9, 2000 version50

170 13.3 Changes to the April 11, 2000 to create the April 26, 2000 version51

171 13.4 Changes to the February 7, 2000 to create the April 11, 2000 version52

172 13.5 Changes to the January 30, 2000 to create the February 7, 2000 version.....54

173 13.6 Changes to the January 28, 2000 to create the January 30, 2000 version54

174 13.7 Changes to create the January 28, 2000 version.....54

175 **14 Appendix B: Possible future additions54**

176 14.1 Possible future keyword additions for "media" and "media-col" attributes55

177 14.2 Possible future additions to the "media-col" Job Template attribute55

178 **15 Appendix C: Description of the IEEE Industry Standards and Technology (ISTO)56**

179 **16 Appendix D: Description of the IEEE-ISTO PWG.....56**

180 **17 Appendix E: IEEE Industry Standards and Technology Organization Copyright Statement .57**

Table of Tables

183

184 Table 1 - Summary of Job Template Attributes 11

185 Table 2 - "cover-front" and "cover-back" member attributes 12

186 Table 3 - "insert-sheet" member attributes 15

187 Table 4 - "job-accounting-sheets" member attributes 18

188 Table 5 - "job-error-sheet" member attributes 20

189 Table 6 - "job-sheets-col" member attributes 23

190 Table 7 - "media-col" member attributes..... 26

191 Table 8 - "media-size" member attributes 31

192 Table 9 - "media-size-supported" member attributes 31

193 Table 10 - "separator-sheets" member attributes 37

194 Table 11 - Job Template Attribute Exception Semantics 43

195 Table 12 - Document and Page Exception Semantics by Attribute..... 43

196

197

198 1 Introduction

199

200 This document specifies an extension to the Internet Printing Protocol/1.0 (IPP) [RFC2565, RFC2566] and
201 IPP/1.1 [ipp-mod, ipp-pro]. This extension consists primarily of Job Template attributes defined for
202 submitting print jobs to production printers. These attributes permit a user to control and/or override
203 instructions in the document content to perform the following functions: print on document covers, insert
204 sheets into the document, provide an accounting id, request accounting sheets, provide job sheet messages,
205 request error sheets, provide a message to the operator, provide a job recipient name in cases that is
206 intended to be different from the job submitter's name, control the media used for job sheets, request media
207 by characteristic (size, weight, etc.), control collation, and shift the image.

208

209 This extension also defines the "current-page-order" Job Description attribute, the "user-defined-names-
210 supported" Printer Description attribute, and the 'resources-are-not-supported' value for the "job-state-
211 reasons" Job Description attribute.

212

213 Some additional "media" keyword values are defined for use with the "media" Job Template attribute.

214

215 Many of these functions MAY be specified in a document format (PDL). In such cases, the user MAY
216 request that the application include these instructions as part of the document data when the document is
217 generated, rather than in the IPP protocol at print time. However, some applications are unable to support
218 some of the functions. Also some of these functions are not supported in some PDLs. Finally, in a
219 production environment, the document may be generated separately from being printed, in which case the
220 end user or the production printer operator supplies the instructions at print time, long after the document
221 had been created.

222

223

224 2 Terminology

225

226 This section defines the following additional terms that are used throughout this document.

227

228 2.1 Conformance Terminology

229

230 Capitalized terms, such as **MUST**, **MUST NOT**, **REQUIRED**, **SHOULD**, **SHOULD NOT**, **MAY**,
231 **NEED NOT**, and **OPTIONAL**, have special meaning relating to conformance to this specification. These
232 terms are defined in [ipp-mod section 13.1 on conformance terminology, most of which is taken from RFC
233 2119 [RFC2119]. Since support of this entire IPP extension specification is **OPTIONAL** for conformance
234 to IPP/1.0 or IPP/1.1 ([ipp-mod], [ipp-pro]), the terms **MUST**, **MUST NOT**, **REQUIRED**, **SHOULD**,
235 **SHOULD NOT**, **MAY**, **NEED NOT**, and **OPTIONAL** apply *if and only if the extension specification in
236 this document is implemented*. Thus a feature labeled as **REQUIRED** in this document is not **REQUIRED**
237 if implementing the basic IPP/1.1 protocol defined by [ipp-mod] and [ipp-pro].

238
239

2.2 Other terminology

document data	The data that represent an "original document" supplied with a Job Creation request. Typically Document Data is in the form of a PDL.
set	The sheets of either (1) one copy of an output document copy with collated sheets or (2) all the copies of a single sheet for uncollated sheets. See description in section 3.13.1.
original document	The document composed by a user that is eventually submitted in the for of Document Data as part of a create request.
original document order	The orders of the pages, typically reading order, as defined in the Original Document.
print-stream pages	The sequence of pages according to the definition of pages in the language used to express the document data defined relative to the Input Document.
Input-Document	The sequence of input pages that the client sends as document data to the IPP Printer (see [ipp-except]).
Output-Document	The sequence of output pages that the Printer renders onto output media (see [ipp-except]).
rendered output	Media sheets that are delivered as part of the output of a print request, typically containing impressions.
collection	An attribute syntax consisting of a set of attributes. Such a collection attribute has a value that is a set of attributes, similar to a Java Map or a PostScript dictionary. See [ipp-coll].

240
241
242
243

2.3 Coordinate System

244 Some of the attribute extensions proposed in this document refer to specific edges of a sheet of printed
245 media. Specifying that a staple be placed in the upper left corner of a printed document is an example. To
246 resolve ambiguity the following coordinate system is used throughout this document:
247

248 The specified edge is always with respect to the document as if the document were a portrait document. If
249 the document is actually a landscape or a reverse-landscape document, the client (which may include a user)
250 supplies the appropriate transformed value. For example, to position a staple in the upper left hand corner
251 of a landscape document when held for reading, the client supplies the 'staple-bottom-left' value (since
252 landscape is defined as a +90 degree rotation from portrait, i.e., anti-clockwise). On the other hand, to
253 position a staple in the upper left hand corner of a reverse-landscape document when held for reading, the
254 client supplies the 'staple-top-right' value (since reverse-landscape is defined as a -90 degree rotation from
255 portrait, i.e., clockwise).
256

257 The x-axis is defined to be along the bottom edge, with positive values extending in the direction of the
258 right edge.
259

260 The y-axis is defined to be along the left edge, with positive values extending toward the top edge.

261

262 The origin (0,0) is the bottom-left corner.

263

264

265 **2.4 Enumeration and Ordering of print-stream pages**

266

267 A *print-stream page* is a page according to the definition of pages in the language used to express the
268 document data" (see section of 13.2.4 of the IPP Model and Semantics Document). The *document data*
269 included in an IPP request is typically a PDL representation of a document composed by a user. For the
270 remainder of this description we will use the term document data to mean the typical PDL representation
271 sent with an IPP request (e.g., a PostScript File), and the term *original document* to mean the document
272 composed by the user (e.g., a Word97 document). The print-stream page numbering is with respect to the
273 Input-Document, not the Output-Document (see [ipp-except]). Furthermore, the page numbers are ordinal
274 numbers starting at 1 and are independent of the page numbers that may be printed on the pages.

275

276 The order of the print-stream pages in the document data is either the same as the order of the original
277 document, known as 1-N (read "one to N"), or the reverse of that order, known as N-1. There are no
278 assumptions on the order of the original document, other than it is ordered.

279

280 The enumeration of print-stream pages begins with 1 and increments by 1 for each additional print-stream
281 page. The enumeration is based on the order of the original document, not the document data supplied with
282 the IPP request. In other words, if the document data is supplied in N-1 order (reverse of the original
283 document order), then print-stream page number '1' in the enumeration is actually the Nth print-stream
284 page defined in the document data (see the "page-order-received" attribute in section 3.12). Similarly,
285 print-stream page number '2' is defined by the (N-1)th print-stream page defined in the document data.
286 Suppose the document data is supplied in the 1-N order (same as the original document order), then print-
287 stream page number '1' in the enumeration is the 1st print-stream page defined in the document data.
288 Similarly, print-stream page number '2' is defined by the 2nd print-stream page defined in the document
289 data. The enumeration of print-stream pages is only relevant when applying attributes or operations that act
290 on a page, or range of page basis (e.g., the "insert-sheet" attribute in section 3.2).

291

292 The enumeration of print-stream pages is affected by the "multiple-document-handling" attribute. When
293 the "multiple-document-handling" attribute is 'single-document' or 'single-document-new-sheet,' the
294 enumeration is based on the concatenation of all the print-stream pages in the job. In the case of 'separate-
295 documents-collated-copies' and 'separate-documents-uncollated-copies,' the enumeration of print-stream
296 pages applies to each document. For example, for a job with eight documents, referring to print-stream
297 page number '1' actually refers to print-stream page number '1' in each of the eight documents included with
298 the job.

299

300 The enumeration of print-stream pages is NOT affected by the "page-ranges" Job Template attribute, if
301 supplied. The "page-ranges" attribute merely affects which Input-Document pages are actually printed. For
302 example, if an insert sheet is to be inserted after print-stream page number is 5 of a 10-page document, the
303 insert page will be inserted after page 5 with respect to the Input-Document as long as page 5 is included in
304 the "page-ranges" attribute. If the "page-ranges" attribute does not include Input-Document page 5, then the
305 insert sheet will not be inserted. Thus a user can supply the "page-ranges" attribute without having to

306 change any other attributes in order to print a part of a document.
307
308

309 **2.5 Collection Attributes**

310

311 An attribute of type 'collection' has a value that is a set of attributes, called *member* attributes. The
312 definition for each member attribute is specified as a sub-section of the collection attribute definition. Each
313 member attribute MAY in turn be single-valued or multi-valued. The Printer validates and processes each
314 member attribute of a Job Template collection attribute in the same way that it validates and processes Job
315 Template attributes. The collection merely serves as a container for the member attributes. In other words,
316 the 'collection' attribute type serves the same purpose as the 'map' data type in the Java programming
317 language and the dictionary mechanism in PostScript. See [ipp-coll] for a complete definition and encoding
318 of the 'collection' attribute syntax with examples.
319

320 **2.6 Definition of 'none' values**

321

322 For most Job Template attributes, the client needs a way to indicate that the Printer MUST NOT perform
323 the feature associated with the attribute, including not performing the default action indicated by the
324 Printer's "xxx-default" attribute. If the client omits the "xxx" Job Template attribute, a corresponding value
325 is used from the PDL data, if present. Otherwise, the Printer's "xxx-default" attribute value is used.
326

327 For each attribute definition, the representation of none is specified or is explicitly disallowed. For string
328 attribute syntax types, such as 'text', 'name', 'uri', 'uriScheme', 'charset', 'naturalLanguage', 'mimeMediaType',
329 and 'octetString', the client supplies a zero-length value to indicate an explicit none. For 'enum', 'keyword',
330 or 'keyword | name' a specific 'none' enum or keyword value is defined. For 'integer' or 'rangeOfInteger'
331 values, a particular distinguished value, such as 0 or -1 is defined to mean none. The client can supply the
332 defined none value in order to override a Printer's "xxx-default" value. The Printer MUST return the 'no-
333 value' out-of-band value for Printer Description attributes that have 'dateTime' or 'integer' time values that
334 do not yet have a value (see [ipp-mod] sections 4.3.14 and 4.4.30).
335

336 Similarly, for the corresponding Printer's "xxx-default", the Printer MUST use the same none value to
337 indicate that there is no default value that will be applied. Thus the defined values for the "xxx-default"
338 attribute are the same as those that a client can supply, including the none case. Consequently, no special
339 mention is made of the none case in each "xxx-default" attribute definition. However, a Printer
340 implementation MUST support the defined none value for each Job Template attribute in job submission,
341 as a value of the "xxx-default" Printer attribute, and as one of the values of the "xxx-supported" Printer
342 attribute, if the Printer supports the "xxx" Job Template attribute. Also the administrator SHOULD be able
343 to remove the 'none' value from the list of supported values if the site policy is to disallow the none case.
344 See [ipp-set-ops] for means to set the values of the "xxx-supported" and "xxx-default" Printer attributes
345 using the Set-Printer-Attributes operation.
346

347 There are a few Job Template attributes for which there is no none value defined, because of the inherent
348 nature of the semantics associated with the attribute the Printer always supplies some value. Examples of
349 such attributes (see [ipp-mod]) are: "media" (type3 keyword | name) and "sides" (keyword). There is no

350 'none' keyword value defined for use with the media and a zero-length string will not match any supported
 351 values. Similarly, there is no 'none' keyword value defined for the "sides" attribute. All jobs that print use
 352 some media instance and either print on one side or on both sides. Thus this kind of attribute does not have
 353 a defined none value. Because some attributes do not have none values defined, while most do, the
 354 definition document MUST specify the distinguished none value in each attribute definition or explicitly
 355 state that there is no distinguished none value.
 356

357 3 Job Template Attributes

358 This section defines Job Template Attribute extensions for production printing. Table 1 summarizes the
 359 Job and Printer Job Template attributes.
 360

361 **Table 1 - Summary of Job Template Attributes**

Job Attribute	Printer: Default Value Attribute	Printer: Supported Values Attribute
cover-back (collection)	cover-back-default (collection)	cover-back-supported (1setOf type2 keyword)
cover-front (collection)	cover-front-default (collection)	cover-front-supported (1setOf type2 keyword)
insert-sheet (collection)	insert-sheet-default (collection)	insert-sheet-supported (1setOf type2 keyword)
job-account-id(name(MAX))	job-account-id-default (name(MAX))	job-account-id-supported (integer(0:255))
job-accounting-sheets (collection)	job-accounting-sheets-default (collection)	job-accounting-sheets-supported (1setOf type2 keyword)
job-error-sheet (collection)	job-error-sheet-default (collection)	job-error-sheet-supported (1setOf type2 keyword)
job-message-to-operator (text(MAX))	job-message-to-operator-default (text(MAX))	job-message-to-operator-supported (integer(0:1023))
job-recipient-name (name(MAX))	job-recipient-name-default (name(MAX))	job-recipient-name-supported (integer(0:255))
job-sheets-col (collection)	job-sheets-col-default (collection)	job-sheets-col-supported (1setOf type2 keyword)
job-sheet-message (text(MAX))	job-sheet-message-default (text(MAX))	job-sheet-message-supported (integer(0:1023))
media-col (collection)	media-col-default (collection)	media-col-supported (1setOf type2 keyword) media-col-ready (1setOf collection)
page-delivery (type2 keyword)	page-delivery-default (type2 keyword)	page-delivery-supported (1setOf type2 keyword)
page-order-received (type2 keyword)	page-order-received-default (type2 keyword)	page-order-received-supported (1setOf type2 keyword)
separator-sheets (collection)	separator-sheets-default (collection)	separator-sheets-supported (1setOf type2 keyword)

x-image-auto-center (boolean)	x-image-auto-center-default (boolean)	x-image-auto-center-supported (boolean)
x-image-shift (integer (MIN:MAX))	x-image-shift-default (integer (MIN:MAX))	x-image-shift-supported (rangeOfInteger (MIN:MAX))
x-side1-image-shift (integer (MIN:MAX))	x-side1-image-shift-default (integer (MIN:MAX))	x-side1-image-shift-supported (rangeOfInteger (MIN:MAX))
x-side2-image-shift (integer (MIN:MAX))	x-side2-image-shift-default (integer (MIN:MAX))	x-side2-image-shift-supported (rangeOfInteger (MIN:MAX))
y-image-auto-center (boolean)	y-image-auto-center-default (boolean)	y-image-auto-center-supported (boolean)
y-image-shift (integer (MIN:MAX))	y-image-shift-default (integer (MIN:MAX))	y-image-shift-supported (rangeOfInteger (MIN:MAX))
y-side1-image-shift (integer (MIN:MAX))	y-side1-image-shift-default (integer (MIN:MAX))	y-side1-image-shift-supported (rangeOfInteger (MIN:MAX))
y-side2-image-shift (integer (MIN:MAX))	y-side2-image-shift-default (integer (MIN:MAX))	y-side2-image-shift-supported (rangeOfInteger (MIN:MAX))

362

363

364 **3.1 cover-front (collection) and cover-back (collection)**

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

These two attributes specify how covers are to be applied to each copy of each printed document within a job. Presence of the "cover-front" attribute indicates that a front cover is requested, and similarly, the presence of the "cover-back" attribute indicates that a back cover is requested. Each of the "cover-front" and "cover-back" attributes includes where printing should be applied on the cover (if any), and what media should be used for the cover.

Both the "cover-front" and "cover-back" attributes are affected by the "multiple-document-handling" attribute. In the case of the 'single-document' and 'single-document-new-sheet' values, the covers MUST be applied to each copy of the composite (single) document. When the value is either 'separate-documents-collated-copies' or 'separate-documents-uncollated-copies', then the covers MUST be applied to each document copy individually.

The sheets in the rendered output that represent the covers are treated like any other sheet in the document copy. For example, if the "finishings" attribute has a value of 'staple,' then the staple would bind the covers, along with all of the other sheets in the output.

Both the "cover-front" and "cover-back" attributes are defined by the following collection:

Table 2 - "cover-front" and "cover-back" member attributes

Attribute name	attribute syntax	request	Printer Support
media	type3 keyword name(MAX)	MAY be neither or one of, but NOT both	MUST

media-col	collection		MAY
cover-type	type2 keyword	MUST	MUST

385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419

3.1.1 media (type3 keyword | name(MAX)) or media-col (collection)

Either the "media" (defined in [ipp-mod] section 4.2.11) or the "media-col" member attribute is used to indicate what media that the Printer MUST use for the specified cover. The member attributes are the same as those for the "media-col" attribute shown in Table 7.

If the client omits both the "media" and the "media-col" member attributes, then the media currently being used by the Printer object for the document copy SHOULD also be used for the cover. The client MUST NOT supply both the "media" and the "media-col" member attributes. If the client supplies such a mal-formed request by supplying both, the Printer MUST either (1) reject the request and return the 'client-error-bad-request' status code (see [ipp-mod] section 13.1.4.1) or (2) use either the "media" or the "media-col" member attribute, independent of the value of the "ipp-attribute-fidelity" attribute supplied by the client.

Since this "media" member attribute has the same name as the "media" Job Template attribute defined in [ipp-mod] section 4.2.11), the "media-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute (also defined in [ipp-mod] section 4.2.11) identifies the values of this "media" member attribute (as well as the values of the "media" Job Template attribute) that the Printer supports, i.e., the names of the supported media.

Since this "media-col" member attribute has the same name as the "media-col" Job Template attribute defined in section 3.10), the "media-col-supported" Printer attribute (defined in section 3.10.16) identifies the keyword names of the member attributes supported in this "media-col" member attribute (as well as the keyword names of the "media-col" Job Template attribute), i.e., the names of the member attributes in Table 7 that the Printer supports.

3.1.2 cover-type (type2 keyword)

The "cover-type" member attribute indicates whether covers are wanted and which sides of the cover MUST contain print-stream pages. The print-stream pages used for printing on a cover come from the document data.

Standard keyword values for "cover-type" are:

'no-cover'	No covers are to be produced.
'print-none'	No printing on either side of the cover.

<p>'print-front'</p>	<p>The front side (side one) of the cover MUST contain a print-stream page.</p> <p>For a front cover ("cover-front") the first print-stream page MUST be placed on side one of the front cover sheet (this is the outside of the front cover). The Printer MUST place the second print stream page on side one of the first sheet of the output document.</p> <p>For back cover ("cover-back") the last print-stream page MUST be placed on side one of the back cover sheet (this is the inside of the back cover). The Printer MUST place the second to last print stream page on the front or back side of the last sheet of the output document depending on whether there are an odd or an even number of print stream pages.</p>
<p>'print-back'</p>	<p>The back side (side two) of the cover MUST contain a print-stream page.</p> <p>For a front cover ("cover-front") the first print-stream page MUST be placed on side two of the front cover sheet (this is the inside of the front cover). The Printer MUST place the second print stream page on side one of the first sheet of the output document.</p> <p>For a back cover ("cover-back") the last print-stream page MUST be placed on side two of the back cover sheet (this is the outside of the back cover). The Printer MUST place the second to last print stream page on the front or back side of the last sheet of the output document depending on whether there are an odd or an even number of print stream pages.</p>
<p>'print-both'</p>	<p>Both the front and back sides of the cover MUST contain a print-stream page.</p> <p>The front cover MUST contain the first and second print-stream pages on the front and back sides of the front cover sheet, respectively. The Printer MUST place the third print stream page on side one of the first sheet of the output document.</p> <p>The back cover MUST contain the second to last and last print-stream pages on the front and back sides of the back cover sheet, respectively. The Printer MUST place the third to last print stream page on the front or back side of the last sheet of the output document depending on whether there are an odd or an even number of print stream pages.</p>

420
421
422
423
424
425
426
427

When printing on the back side (side two) of a cover, the value of the "sides" attribute **SHOULD** be used to determine which edge is the reference edge (i.e., long or short edge). In the case where the "sides" attribute is 'one-sided,' then the reference edge **SHOULD** be the long edge.

NOTE: If referencing the "sides" attribute is insufficient for determining the reference edge printing on the back side of a cover, then an additional member attribute could be defined that indicates which edge to reference. However, the predominate use cases are covered without this additional

428 member attribute.

429
430 In cases where the document data does not contain enough print-stream pages to satisfy the "cover-
431 front" or "cover-back" request, the behavior is implementation dependent.

432
433 The "cover-type-supported" (1setOf type2 keyword) Printer attribute identifies the values that the
434 Printer supports, i.e., the keyword cover types supported.

435
436 **3.1.3 cover-front-default (collection) and cover-back-default (collection)**

437
438 The "cover-front-default" and "cover-back-default" specify the cover that the Printer will provide, if
439 any, if the client omits the "cover-front" or "cover-back" Job Template attribute, respectively. The
440 member attributes are defined in Table 2. A Printer MUST support the same member attributes and
441 values for these default attributes as it supports for the corresponding "cover-front" and "cover-
442 back" Job Template attributes.

443
444 **3.1.4 cover-front-supported (1setOf type2 keyword), cover-back-supported (1setOf type2
445 keyword)**

446
447 The "cover-front-supported" and "cover-back-supported" attributes identify the keyword names of
448 the member attributes supported in the "cover-front" and "cover-back" collection Job Template
449 attributes, respectively, i.e., the keyword names of the member attributes in Table 2 that the Printer
450 supports.

451
452 **3.2 insert-sheet (1setOf collection)**

453
454 This attribute specifies how sheets that are not to be imaged, are to be inserted into the sequence of media
455 sheets that are produced for each copy of each printed document in the job. How the sheet is inserted is
456 implementation dependent, and could be as sophisticated as insertion hardware, or as simple as using media
457 from an existing input-tray.

458
459 The order of the values of the "insert-sheet" attribute is important. In the case where more than one value
460 refers to the same page (i.e., multiple values contain the same value for the "after-page-number" member
461 attribute), the values of "insert-sheet" are to be applied in the order that they occur.

462
463 This attribute is affected by the "multiple-document-handling" attribute. For values of 'single-document'
464 and 'single-document-new-sheet,' the sheet is inserted in the composite (single) document created by the
465 concatenation of all the print-stream pages in all of the documents. In the case of 'separate-documents-
466 collated-copies' and 'separate-documents-uncollated-copies,' the inserted sheets are applied to the print-
467 stream in each document separately. The collection consists of:

468
469 **Table 3 - "insert-sheet" member attributes**

Attribute name	attribute syntax	request	Printer Support
----------------	------------------	---------	-----------------

insert-after-page-number	integer (0:MAX)	MUST	MUST
insert-count	integer (0:MAX)	MAY	MUST
media	type3 keyword name(MAX)	MUST be one or the other, but NOT both	MUST
media-col	collection		MAY

470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509

3.2.1 insert-after-page-number (integer(0:MAX))

The "insert-after-page-number" member attribute specifies the page in the Input-Document (see sections 2.2 and 2.4) print-stream after which the sheet is to be placed. The inserted sheet(s) does not affect the number of print-stream pages. For-example, to insert a single sheet after both pages 2 and 3 of a given document, the value of "input-after-page-number" would be 2 and 3 respectively (not 2 and 4, as it would be if the inserted sheet affected the Input-Document print-stream page count). For a complete description of the enumeration of print-stream pages see section 2.4.

If the value of the "insert-after-page-number" member attribute is 0, then the sheet is inserted before the first page. If the value is MAX, then the sheet is inserted after the last sheet in the document.

If the "insert-after-page-number" member attribute is not a valid input document page reference in the print-stream, then the IPP Printer SHOULD ignore the request. For example, (1) the page number is beyond the last page of the document AND is not MAX or (2) the "page-ranges" Job Template attribute does not include the specified page number (see section 2.4). There is no way to validate the "after-page-number" attribute with the Validate-Job operation, since the validation cannot occur until the pages of the documents have arrived at the printer.

Since the "insert-after-page-number" member attribute refers to a specific input-document print-stream page, it is possible to specify an insertion between sides one and two, of a two sided document, or between print-stream pages that are part of a single impression if the "number-up" attribute has a value other than '1.' In this case, the Printer MUST force a new Sheet after the specified page, insert the specified sheet, place the following pages on the first side of the next Sheet, and issue a warning by adding 'job-warnings-detected' to the "job-state-reasons" and by increasing the value of the "job-warnings-count" Job Description attribute by 1. See [ipp-except] for this error handling specification under "Common Behavior for Sheet Attributes".

The "insert-after-page-number-supported" (rangeOfInteger(0:MAX)) Printer attribute indicates the range of page numbers supported in the "insert-after-page-number" member attribute, i.e., the minimum (SHOULD be 0) and the maximum (SHOULD be MAX) page numbers supported.

3.2.2 insert-count (integer(0:MAX))

The "insert-count" attribute indicates how many sheets to insert. If the "insert-count" attribute is omitted, then the printer assumes a value of 1. The value 0 indicates that no inserts sheets are to be inserted.

510 The "insert-count-supported (rangeOfInteger(0:MAX)) Printer attribute specifies the range of values
511 that the Printer supports, i.e., the minimum number (MUST be 0) and the maximum number of
512 pages.
513

514 **3.2.3 media (type3 keyword | name(MAX)) or media-col (collection)**

515
516 Either the "media" (defined in [ipp-mod] section 4.2.11) or the "media-col" member attribute is used
517 to indicate the media that the Printer MUST use for the insert sheet. The member attributes are the
518 same as those for the "media-col" attribute shown in Table 7.
519

520 The client MUST supply either the "media" or the "media-col" member attribute, but NOT both. If
521 the client supplies such a mal-formed request by supplying neither or both, the Printer MUST
522 (depending on implementation) either (1) reject the request and return the 'client-error-bad-request'
523 status code (see [ipp-mod] section 13.1.4.1) or (2) use either the "media" or the "media-col" member
524 attribute, independent of the value of the "ipp-attribute-fidelity" attribute supplied by the client.
525

526 Since this "media" member attribute has the same name as the "media" Job Template attribute
527 defined in [ipp-mod] section 4.2.11), the "media-supported" (1setOf (type3 keyword | name(MAX)))
528 Printer attribute (also defined in [ipp-mod] section 4.2.11) identifies the values of this "media"
529 member attribute (as well as the values of the "media" Job Template attribute) that the Printer
530 supports, i.e., the names of the supported media.
531

532 Since this "media-col" member attribute has the same name as the "media-col" Job Template
533 attribute defined in section 3.10), the "media-col-supported" Printer attribute (defined in section
534 3.10.16) identifies the keyword names of the member attributes supported in this "media-col"
535 member attribute (as well as the keyword names of the "media-col" Job Template attribute), i.e., the
536 names of the member attributes in Table 7 that the Printer supports.
537

538 **3.2.4 insert-sheet-default (1setOf collection)**

539
540 The "insert-sheet-default" Printer attributes specify the insert sheet(s) that the Printer MUST
541 provide, if any, if the client omits the "insert-sheet" Job Template attribute. The member attributes
542 are defined in Table 3. A Printer MUST support the same member attributes for this default
543 collection attribute as it supports for the corresponding "insert-sheet" Job Template attribute.
544

545 **3.2.5 insert-sheet-supported (1setOf type2 keyword)**

546
547 The "insert-sheet-supported" attribute identifies the keyword names of the member attributes
548 supported in the "insert-sheet" collection Job Template attribute, i.e., the keyword names of the
549 member attributes in Table 3 that the Printer supports.
550
551
552

553 **3.3 job-account-id (name (MAX))**

555 The "job-account-id" attribute is a character string representing the account associated with the job. The
 556 "job-account-id" attribute could be a customer name, a sequence of digits referencing an internal billing
 557 number, or even a credit card number. How the printer uses the "job-account-id" is implementation
 558 dependent. A zero-length value indicates that there is no account name.
 559
 560

561 **3.3.1 job-account-id-supported (integer(1:255))**

562 The "job-account-id-supported" attribute indicates the maximum length that the Printer will accept
 563 for the "job-account-id" Job Template attribute without truncation. A conforming Printer MUST be
 564 able to accept 255 octets without truncation. However, an IPP Printer MAY be implemented as a
 565 gateway to another print system that cannot accept the full 255-octet range, in which case the value
 566 will be truncated to the maximum length specified by the "job-account-id-supported" attribute.
 567
 568
 569

570 **3.4 job-accounting-sheets (collection)**

571 This attribute specifies which job accounting sheets MUST be printed with the job. Job accounting sheets
 572 typically contain information such as the value of the "job-account-id" attribute, and the number and type of
 573 media sheets used while printing the job. The exact information contained on a job accounting sheet is
 574 implementation dependent, but should always be a reflection of the account information associated with the
 575 job.
 576
 577

578 The 'collection' syntax allows a client to specify media for job accounting sheets that is different than the
 579 current media being used for the print-stream page impressions. The collection consists of:
 580

581 **Table 4 - "job-accounting-sheets" member attributes**

Attribute name	attribute syntax	request	Printer Support
job-accounting-sheets-type	type3 keyword name(MAX)	MUST	MUST
media	type3 keyword name(MAX)	MAY be	MUST
media-col	collection	neither or one of, but NOT both	MAY

582
 583
 584 **3.4.1 job-accounting-sheets-type (type3 keyword | name(MAX))**
 585

586 The "job-accounting-sheets-type" member attribute specifies which job accounting sheets format the
 587 Printer MUST use to print on the specified media. Standard keyword values are:
 588

'none'	No accounting sheets are to be printed (i.e. printing of job accounting sheets is totally suppressed).
'standard'	The standard site accounting sheet MUST be printed with the job.

589
590 The "job-accounting-sheets-type-supported" (1setOf (type3 keyword | name(MAX))) Printer
591 attribute identifies the values of this "job-accounting-sheets-type" member attribute that the Printer
592 supports, i.e., the names of the job accounting sheets supported.
593

594 **3.4.2 media (type3 keyword | name(MAX)) or media-col (collection)**

595
596 Either the "media" (defined in [ipp-mod] section 4.2.11) or the "media-col" member attribute is used
597 to indicate the media that the Printer SHOULD use for the job accounting sheet. The member
598 attributes are the same as those for the "media-col" attribute shown in Table 7.
599

600 If both the "media" and the "media-col" member attributes are omitted, then the media currently
601 being used by the Printer object for the document copy SHOULD also be used for the accounting
602 sheet. The client MUST NOT supply both the "media" and the "media-col" member attribute. If the
603 client supplies such a mal-formed request by supplying both, the Printer MUST (depending on
604 implementation) either (1) reject the request and return the 'client-error-bad-request' status code (see
605 [ipp-mod] section 13.1.4.1) or (2) use either the "media" or the "media-col" member attribute,
606 independent of the value of the "ipp-attribute-fidelity" attribute supplied by the client.
607

608 Since this "media" member attribute has the same name as the "media" Job Template attribute
609 defined in [ipp-mod] section 4.2.11), the "media-supported" (1setOf (type3 keyword | name(MAX)))
610 Printer attribute (also defined in [ipp-mod] section 4.2.11) identifies the values of this "media"
611 member attribute (as well as the values of the "media" Job Template attribute) that the Printer
612 supports, i.e., the names of the media supported.
613

614 Since this "media-col" member attribute has the same name as the "media-col" Job Template
615 attribute defined in section 3.10), the "media-col-supported" Printer attribute (defined in section
616 3.10.16) identifies the keyword names of the member attributes supported in this "media-col"
617 member attribute (as well as the keyword names of the "media-col" Job Template attribute), i.e., the
618 names of the member attributes in Table 7 that the Printer supports.
619

620 **3.4.3 job-accounting-sheets-default (collection)**

621
622 The "job-accounting-default" Printer attributes specify the job accounting that the Printer MUST
623 provide, if any, if the client omits the "job-accounting" Job Template attribute. The member
624 attributes are defined in Table 4. A Printer MUST support the same member attributes and value
625 for this default collection attribute as it supports for the corresponding "job-accounting-sheets" Job
626 Template attribute.
627

628 **3.4.4 job-accounting-sheets-supported (1setOf type2 keyword)**

629
630 The "job-accounting-supported" attribute identifies the keyword names of the member attributes
631 supported in the "job-accounting-sheets" Job Template collection attribute, i.e., the keyword names
632 of the member attributes in Table 4 that the Printer supports.
633

634 **3.5 job-error-sheet (collection)**

635

636 This attribute specifies which job error sheet **MUST** be printed with the job. This is a printer specific sheet
 637 enumerating any known errors or warnings that occurred during processing. For example: a printer could
 638 put the text 'warning: image off page 2,' on the error sheet to indicate a possible image processing defect.
 639 The printer vendor defines the content of the error sheet. If necessary the error sheet can consist of more
 640 than one page of output.

641

642 If the Printer is producing a job sheet for this job (see section 3.8 and [ipp-mod] section 4.2.3), then the
 643 Printer object **MAY** print any error and warning information on that same job sheet, i.e., merge the error
 644 sheet with the job sheet. This use of the job sheet for errors only applies if the "job-error-sheet" attribute is
 645 supplied without either a "media" or "media-col" member attribute. If the "media" or "media-col" member
 646 attribute is supplied, a separate error sheet **MUST** always be used to print errors and warnings.

647

648 The 'collection' syntax allows a client to specify media for job error sheets that is different than the current
 649 media being used for the print-stream page impressions. The collection consists of:

650

651

Table 5 - "job-error-sheet" member attributes

Attribute name	attribute syntax	request	Printer Support
job-error-sheet-type	type3 keyword name(MAX)	MUST	MUST
job-error-sheet-when	type2 keyword	MAY	MAY
media	type3 keyword name(MAX)	MAY be neither or one of, but NOT both	MUST
media-col	collection		MAY

652

653

654

3.5.1 job-error-sheet-type (type3 keyword | name(MAX))

655

656

657

The "job-error-sheet-type" member attribute specifies which job error sheets format that the Printer **SHOULD** to print error information. Standard keyword values are:

'none'	No error sheet information is to be printed. (i.e., printing of error sheets is totally suppressed – even if errors or warnings occurred during job processing).
'standard'	The standard site or vendor defined error sheet information MUST be printed with the job depending on the conditions specified by the "job-error-sheet-when" attribute.

658

659

660

661

662

The "job-error-sheet-type-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute identifies the values of this "job-error-sheet-type" member attribute that the Printer supports, i.e., the names of the job error sheets.

663

664

665

3.5.2 job-error-sheet-when (type2 keyword)

The "job-error-sheet-when" member attribute specifies the conditions under which the error sheet

666 information is to be produced. The standard keyword values are:
 667

'on-error'	Print the error sheet information if and only if errors or warnings occurred during the life of the job.
'always'	Always print the error sheet information, i.e., error sheets are printed even if no errors or warnings occurred during job processing – when no errors or warnings occurred a suitable message will be printed on the sheet to indicate this. The 'always' value gives an explicit indication of whether or not there were errors or warnings detected during the processing of the job.

668
 669 The "job-error-sheet-when-supported" (1setOf type2 keyword) Printer attribute identifies the values
 670 of this "job-error-sheet-when" member attribute that the Printer supports, i.e., the possible
 671 conditions under which the job error sheet will be printer.
 672

673 **3.5.3 media (type3 keyword | name(MAX)) or media-col (collection)**
 674

675 Either the "media" (defined in [ipp-mod] section 4.2.11) or the "media-col" member attribute is used
 676 to indicate the media that the Printer SHOULD be use for the job error sheets. The member
 677 attributes are the same as those for the "media-col" attribute shown in Table 7.
 678

679 If the client omits both of the "media" or the "media-col" member attributes, the Printer prints any
 680 job sheet error information on either the job sheet, if it is being produced, or a separate sheet using
 681 the media of the document, depending on implementation.
 682

683 The client MUST NOT supply both the "media" and the "media-col" member attribute. If the client
 684 supplies such a mal-formed request by supplying both, the Printer MUST (depending on
 685 implementation) either (1) reject the request and return the 'client-error-bad-request' status code (see
 686 [ipp-mod] section 13.1.4.1) or (2) use either the "media" or the "media-col" member attribute,
 687 independent of the value of the "ipp-attribute-fidelity" attribute supplied by the client.
 688

689 Since this "media" member attribute has the same name as the "media" Job Template attribute
 690 defined in [ipp-mod] section 4.2.11), the "media-supported" (1setOf (type3 keyword | name(MAX)))
 691 Printer attribute (also defined in [ipp-mod] section 4.2.11) identifies the values of this "media"
 692 member attribute (as well as the values of the "media" Job Template attribute) that the Printer
 693 supports, i.e., the names of the supported media.
 694

695 Since this "media-col" member attribute has the same name as the "media-col" Job Template
 696 attribute defined in section 3.10), the "media-col-supported" Printer attribute (defined in section
 697 3.10.16) identifies the keyword names of the member attributes supported in this "media-col"
 698 member attribute (as well as the keyword names of the "media-col" Job Template attribute), i.e., the
 699 names of the member attributes in Table 7 that the Printer supports.
 700

701 **3.5.4 job-error-sheet-default (collection)**
 702

703 The "job-error-sheet-default" Printer attributes specify the job error sheets that the Printer MUST

704 provide, if any, if the client omits the "job-error-sheet" Job Template attribute. The member
705 attributes are defined in Table 5. A Printer MUST support the same member attributes and values
706 for this default attribute as it supports for the corresponding "job-error-sheet" Job Template
707 attribute.

708
709 An implementation SHOULD be configured out-of-the-box so that the "job-error-sheet-default"
710 Printer Attribute has the collection value consisting of the "job-error-sheet-type" with a value of:
711 'standard' rather than 'none'. Then the Administrator and End Users have to explicitly turn off error
712 information.

713 **3.5.5 job-error-sheet-supported (1setOf type2 keyword)**

714
715
716 The "job-error-sheet-supported" attribute identifies the names of the member attributes supported in
717 the "job-error-sheet" Job Template collection attribute, i.e., the keyword names of the member
718 attributes in Table 5 that the Printer supports.

719 **3.6 job-message-to-operator (text(MAX))**

720
721
722 This attribute carries a message from the user to the operator to indicate something about the processing of
723 the print job. A zero length text value indicates no message.

724
725
726 Note: this attribute may be used in conjunction with the IPP 1.0 "job-hold-until" Job Template attribute
727 (see [ipp-mod] section 4.2.2); specifically with the 'indefinite' value. This combination allows a client to
728 specify instructions to the operator, while simultaneously preventing the job from being processed until
729 some operator intervention occurs. This combination is particularly useful in production printing
730 environments, where printer configuration may be required to properly print the job.

731 **3.6.1 job-message-to-operator-supported (integer(0:1023))**

732
733
734 The "job-message-to-operator-supported" Printer attribute indicates the maximum length that the
735 Printer will accept for the "job-message-to-operator" Job Template attribute without truncation. A
736 conforming Printer MUST be able to accept 1023 octets without truncation. However, an IPP
737 Printer MAY be implemented as a gateway to another print system that cannot accept the full 1023
738 octet range, in which case the value will be truncated to the maximum length specified by the "job-
739 message-to-operator-supported" attribute.

740 **3.7 job-recipient-name (name(MAX))**

741
742
743 This attribute contains the name of the person that is to receive the output of the job. The value of the "job-
744 recipient-name" attribute is commonly printed on job sheets printed with the job. An example of another
745 use of the "job-recipient-name" attribute is if the printer accesses a database to get job delivery instructions
746 for the recipient of a job. A zero-length value indicates that there is no job recipient name.
747

748

749 If the client omits this attribute in a create request, the printer MAY use the "job-recipient-name-default"
 750 attribute value, unless it has not been configured by the administrator, or MAY use the "authenticated user"
 751 name (see [IPP-MOD] section 8.3), depending on implementation.

752

753 **3.7.1 job-recipient-name-supported (integer(0:255))**

754

755 The "job-recipient-name-supported" Printer attribute indicates the maximum length that the Printer
 756 will accept for the "job-recipient-name" Job Template attribute without truncation. A conforming
 757 Printer MUST be able to accept 255 octets without truncation. However, an IPP Printer MAY be
 758 implemented as a gateway to another print system that cannot accept the full 255 octet range, in
 759 which case the value will be truncated to the maximum length specified by the "job-recipient-name-
 760 supported" attribute.

761

762

763 **3.8 job-sheets-col (collection) - augments IPP/1.1 "job-sheets"**

764

765 This attribute augments the IPP/1.1 "job-sheets" attribute (define in [ipp-mod] section 4.2.3). The
 766 'collection' attribute syntax allows a client to specify media for job sheets that is different than the current
 767 media being used for the print stream images. An example of where this is useful is for separator sheets,
 768 which may allow easier distinction of document copies.

769

770 Table 6 lists the member attributes of the "job-sheets-col" collection attribute:

771

772

Table 6 - "job-sheets-col" member attributes

Attribute name	attribute syntax	request	Printer Support
job-sheets	type3 keyword name(MAX)	MUST	MUST
media	type3 keyword name(MAX)	MUST be one or the other, but NOT both	MUST
media-col	collection		MAY

773

774 **3.8.1 job-sheets (type3 keyword | name(MAX))**

775

776 The "job-sheets" member attribute specifies which job sheets to print on the specified media. The
 777 values for this member attribute are identical to the keyword and name values for the "job-sheets"
 778 Job Template attribute itself, including the 'none' value, and convey the same semantics.

779

780 Since this "job-sheets" member attribute has the same name as the "job-sheets" Job Template
 781 attribute defined in [ipp-mod] section 4.2.3), the "job-sheets-supported" (1setOf (type3 keyword |
 782 name(MAX))) Printer attribute specifies which are the values of this "job-sheets" member attribute
 783 (as well as the values of the IPP/1.1 "job-sheets" Job Template attribute) that the Printer supports.

784

3.8.2 media (type3 keyword | name(MAX)) or media-col (collection)

Either the "media" (defined in [ipp-mod] section 4.2.11) or the "media-col" member attribute is used to indicate the media that the Printer SHOULD use for the job sheet. The member attributes are the same as those for the "media-col" attribute shown in Table 7.

The client MUST supply either the "media" or the "media-col" member attribute, but NOT both. If the client supplies such a mal-formed request by supplying neither or both, the Printer MUST (depending on implementation) either (1) reject the request and return the 'client-error-bad-request' status code (see [ipp-mod] section 13.1.4.1) or (2) use either the "media" or the "media-col" member attribute, independent of the value of the "ipp-attribute-fidelity" attribute supplied by the client.

Since this "media" member attribute has the same name as the "media" Job Template attribute defined in [ipp-mod] section 4.2.11), the "media-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute (also defined in [ipp-mod] section 4.2.11) identifies the values of this "media" member attribute (as well as the values of the "media" Job Template attribute) that the Printer supports, i.e., the names of the supported media.

Since this "media-col" member attribute has the same name as the "media-col" Job Template attribute defined in section 3.10), the "media-col-supported" Printer attribute (defined in section 3.10.16) identifies the keyword names of the member attributes supported in this "media-col" member attribute (as well as the keyword names of the "media-col" Job Template attribute), i.e., the names of the member attributes in Table 7 that the Printer supports.

3.8.3 job-sheets-col-default (collection)

The "job-sheets-default" (see [ipp-mod] section 4.2.3) attribute and the "job-sheets-col-default" Printer attribute specify the job sheets that the Printer MUST provide, if the client omits both the "job-sheets" and the "job-sheets-col" Job Template attribute in the Job Creation operation (and the PDL doesn't include a job sheets specification). The member attributes are defined in Table 6. A Printer MUST support the same member attributes for this default collection attribute as it supports for the corresponding "job-sheets-col" Job Template attribute.

The "job-sheets-default" and "job-sheets-col-default" Printer attributes MUST both be configured to specify the same job sheet instance. If the administrator sets one of them to a value (either locally or with the Set-Printer-Attributes operation - see [ipp-set]), the Printer MUST set the other attribute's value to specify the same job sheet instance or to the 'unknown' out-of-band value, if there isn't a corresponding value to be set for the other attribute. If a client attempts to set both attributes, but their values specify different job sheet instances, the Printer MUST reject the Set-Printer-Attributes operation and return the 'client-error-conflicting-attributes' status code. The reason to have both default attributes configured, is so that clients that only know about the "job-sheets" attribute will see the "job-sheets-default" attribute, while clients that know about the "job-sheets-col" attribute will be able to determine the characteristics of the job sheet default.

3.8.4 job-sheets-col-supported (1setOf type2 keyword)

The "job-sheets-col-supported" attribute identifies the keyword names of the member attributes supported in the "job-sheets-col" collection Job Template attribute, i.e., the keyword names of the member attributes in Table 6 that the Printer supports.

3.9 job-sheet-message (text(MAX))

This attribute is used to convey a message that is delivered with the job, and may be printed on a job sheet (e.g., the 'standard' job sheet). The message may contain any type of information, but typically includes either instructions for offline processing (e.g., finishing), or a message for the job recipient.

3.9.1 job-sheet-message-supported (integer(0:1023))

The "job-sheet-message-supported" Printer attribute indicates the maximum length that the Printer is able to accept for the "job-sheet-message" Job Template attribute without truncation. A conforming Printer MUST be able to accept 1023 octets without truncation. However, an IPP Printer MAY be implemented as a gateway to another print system that cannot accept the full 1023 octet range, in which case the value will be truncated to the maximum length specified by the "job-sheet-message-supported" attribute.

3.10 media-col (collection) - augments IPP/1.1 "media"

This attribute augments the "media" Job Template attribute (defined in [ipp-mod] section 4.2.11). This collection attribute enables a client end user to submit a list of media characteristics to the Printer as a way to more completely specify the media for the Printer to be used. Each member attribute of the collection identifies a media characteristic. A Printer MAY support the "media" attribute without supporting the "media-col" attribute. However, if a Printer supports the "media-col" attribute, it MUST also support the "media" attribute.

Each value of the "media" (type3 keyword | name) attribute uniquely identifies an instance of media. Each combination of values of the "media-col" collection attribute also uniquely identify an instance of media. Depending on implementation and site policy, not all media instances need have media names. Such media instances that do not have media names associated with them are accessible using the "media-col" attribute only. In other words, when a media data base is created by an implementation and/or an administrator, each media name is associated with a media instance, but each media instance NEED NOT have a media name associated with it. Thus the standard name 'iso-a4-white' is associated with a particular instance of media, say, a 20 pound, 210 mm x 297 mm size, and white color media instance. If there are other media instances of the same size and color, but differ in some other characteristic, such as weight, then they MUST each have different names or not have a name at all. A Printer MUST NOT have two instances of media that have all of the same characteristics. The "media-description" member attribute (see section 3.10.1) MUST be used to distinguish two or more media instances that would otherwise have the same characteristics.

873

874 When associating standard media keywords with media instances to be used with the "media" attribute, the
 875 implementation and/or the administrator SHOULD associate them with media instances whose
 876 characteristics are what users would normally expect. For example, the 'iso-a4-white' keyword SHOULD
 877 be associated with a media instance that is A4 in size, 20 pound or 24 pound in weight, white in color, with
 878 an opaque opacity, no holes, no tabs, etc.

879

880 The standard media keywords that identify media sizes, such as 'iso-a4' and 'na-letter', are associated with
 881 any media in an input tray that is configured for that media size. Thus specifying media size keywords with
 882 the "media" attribute does not guarantee reproducible results from one job submission to another, since
 883 different media of the same size may be present from one time to the next. If none of the input trays are
 884 configured for that size, the association with a media instance is implementation dependent.

885

886 The client MUST NOT supply both the "media" and the "media-col" Job Template attributes in a Job
 887 Creation request. If the client supplies such a mal-formed request by supplying both, the Printer MUST
 888 (depending on implementation) either (1) reject the request and return the 'client-error-bad-request' status
 889 code (see [ipp-mod] section 13.1.4.1) or (2) use either the "media" or the "media-col" attribute, independent
 890 of the value of the "ipp-attribute-fidelity" attribute supplied by the client.

891

892 A number of collection Job Template attributes defined in this document have both the "media" and
 893 "media-col" member attributes. The same rule against supplying both in a request holds for these collection
 894 attributes. Those Job Template attributes whose sole purpose is to specify the media are defined so that the
 895 Printer MUST use the requested media, while those that have additional purposes as well are defined so
 896 that the Printer SHOULD use the requested media.

897

898 Table 7 lists the member attributes of the "media-col" collection attribute:

899

900

Table 7 - "media-col" member attributes

Attribute name	attribute syntax	request	Printer Support
media-description	type3 keyword name(MAX)	MAY	MAY
media-color	type3 keyword name(MAX)	MAY	MAY
media-opacity	type3 keyword	MAY	MAY
media-pre-printed	type3 keyword name	MAY	MAY
media-tabs	type3 keyword	MAY	MAY
media-hole-count	integer(0:MAX)	MAY	MAY
media-order-count	integer(1:MAX)	MAY	MAY
media-label-type	type3 keyword name(MAX)	MAY	MAY
media-size	collection	MAY	MUST
media-weight-metric	integer(0:MAX)	MAY	MAY
media-weight-english	integer(0:MAX)	MAY	MAY
media-back-coating	type3 keyword name(MAX)	MAY	MAY
media-front-coating	type3 keyword name(MAX)	MAY	MAY

media-recycled	type3 keyword name(MAX)	MAY	MAY
----------------	---------------------------	-----	-----

901
902 When media is specified by characteristic using the 'collection' attribute syntax, the printer object MUST
903 match the requested media exactly. The "media-col" collection member attributes definitions are:
904
905

906 **3.10.1 media-description (type3 keyword | name(MAX))**

907
908 The "media-description" member attribute is used to specify a media description. The "media-
909 description" member attribute is treated as just another characteristic of the media that the printer
910 must match to select the correct media. Furthermore, more than one medium instance can have the
911 same 'keyword' or 'name' value. As with any 'keyword | name' value, the client SHOULD localize
912 the 'keyword' value, but not the 'name' value.
913

914 The value of the "media-description" member attribute can be any of the keyword or name values
915 defined for the "media" Job Template attribute (see [ipp-mod] section 4.2.11 and section 6.3 in this
916 document) or any other name value defined by the implementation or administrator that is a
917 description. But, unlike the "media" attribute 'keyword' values, the 'keyword' value of the "media-
918 description" member attribute MUST have no specific semantic meaning to the Printer. For
919 example, if the keyword value is one of the input tray keywords, the Printer MUST NOT use that
920 value to pull the media from that tray. If the client wants to select the media in a particular tray, no
921 matter what it is, then the client MUST supply that tray keyword name, say, 'top', in the "media" Job
922 Template attribute, instead of using the "media-description" member attribute. Similarly, if the text
923 string happens to be the same as one of the media size names, the Printer MUST NOT use that value
924 to select a media of that size. When supplying the "media-col" attribute, the client MUST use the
925 "media-size" member attribute to specify the size. If the client wants to select the media of a
926 particular size, no matter what it is, then the client MUST supply that size keyword name, say 'iso-
927 a4', in the "media" Job Template attribute, instead of using the "media-description" member
928 attribute.
929

930 For example, suppose that a Printer supports two A4 media that are identical, except that one has
931 three punched holes and the other does not. If the "media-hole-count" member attribute (see section
932 3.10.6) is supported, then one will have the value, say, '3' and the other '0'. In such a case, the
933 "media-description" attribute is not needed to distinguish between the two media instances.
934 However, if the "media-hole-count" member attribute is not supported, the "media-description"
935 MUST have different values for the two media, say, 'punched' and 'un-punched' (or a zero length
936 'name' string), respectively. The "media-description" member attribute could contain any additional
937 information, such as the size, weight, color, etc. However, the client cannot localize any 'name'
938 values (only pre-defined standard 'keyword' values) to the locale of the user. In order to allow the
939 users to access these two media instances most simply using the "media" attribute, they SHOULD
940 each have names associated with them, such as the 'iso-a4-punched' name (defined by the
941 administrator) and the 'iso-a4-white' keyword (defined in IPP/1.1 - see [ipp-mod] Appendix C).
942

943 As another example of the use of the "media-description" member attribute to distinguish two media
944 instances that otherwise would have identical characteristics, there are a number of IPP/1.1 media

945 keywords that a user would expect to have the same characteristics. For example, 'na-letter' and 'a'
 946 are both 8.5 by 11 inches. If they would be associated with media instances that have the same
 947 characteristics, the administrator MUST put two different values in their "media-description"
 948 member attributes, say, 'na-letter' and 'a'.
 949

950 The "media-description-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute
 951 identifies the values of this "media-description" member attribute that the Printer supports, i.e., the
 952 descriptions supported.
 953

954 **3.10.2 media-color (type3 keyword | name(MAX))**

955 The "media-color" attribute indicates the desired color of the media being specified.
 956

957 Standard keyword values for "media-color" are:
 958
 959

'clear'	The specified media should have no color.
'white'	The specified media should be white.
'pink'	The specified media should be pink.
'yellow'	The specified media should be yellow.
'blue'	The specified media should be blue.
'green'	The specified media should be green.
'buff'	The specified media should be buff.
'goldenrod'	The specified media should be goldenrod.
'red'	The specified media should be red.
'gray'	The specified media should be gray.
'ivory'	The specified media should be ivory.
'orange'	The specified media should be orange.

960 Note: The standard keyword values for the "media-color" attribute are derived primarily from the
 961 Printer MIB [RFC1759] prtInputMediaColor standard values with the addition of 'blue', 'red', 'gray',
 962 'ivory', 'orange', and 'clear' (instead of 'transparent' - see section 3.10.3).
 963
 964

965 Custom paper colors can be specified using the 'name' (MAX) attribute syntax of the color attribute.
 966

967 The "media-color-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute identifies the
 968 values of this "media-color" member attribute that the Printer supports, i.e., the colors supported.
 969

970 **3.10.3 media-opacity (type3 keyword)**

971 The "media-opacity" attribute indicates the desired opaqueness of the media being specified.
 972

973 Standard keyword values for "opacity" are:
 974
 975

'opaque'	The specified media should be opaque.
----------	---------------------------------------

'transparent'	The specified media should be transparent.
---------------	--

The "media-opacity-supported" (1setOf type3 keyword) Printer attribute identifies the values of this "media-opacity" member attribute that the Printer supports, i.e., the opacities supported.

3.10.4 media-pre-printed (type3 keyword | name(MAX))

The "media-pre-printed" attribute indicates that the pre-printed characteristics of the desired media. Examples of pre-printed media include forms and company letterhead. If the value is 'blank', the Printer MAY use an electronic representation of a form, if the medium has some imaged information already associated with it. The standard keyword values for "media-pre-printed" are:

'blank'	The desired medium is not pre-printed.
'pre-printed'	The desired medium is pre-printed; the other attributes identify which medium instance and so what is actually pre-printed.
letter-head'	The site-defined letter head pre-printed is desired.

The "media-pre-printed-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute identifies the values of this "media-pre-printed" member attribute that the Printer supports.

3.10.5 media-tabs (type3 keyword)

The "media-tabs" member attribute indicates that the desired media should have tabs.

Standard keyword values for "media-tabs" are:

'none'	There are no tabs on the desired media
'pre-cut'	The desired media has tabs, each of which extends only partially along a given edge.
'full-cut'	The desired media has tabs which extend along the entire length of a given edge.

The "media-tabs" member attribute does not imply that media is ordered in any way. Ordered media is specified only using the "media-order-count" member attribute (see section 3.10.7). If the tabbed media is ordered, then the order MUST be indicated using the "media-order-count" member attribute.

The "media-tabs-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute identifies the values of this "media-tabs" member attribute that the Printer supports, i.e., the tabs supported.

3.10.6 media-hole-count (integer(0:MAX))

The "media-hole-count" attribute indicates the number of pre-drilled holes in the desired media. A value of 0 (zero) indicates that no holes should be present in the media.

The "media-hole-count-supported" (1setOf rangeOfInteger(0:MAX)) Printer attribute identifies the ranges of values of this "media-hole-count" member attribute that the Printer supports.

3.10.7 media-order-count (integer(1:MAX))

The "media-order-count" attribute indicates the number of sheets, within an ordered sequence of sheets; after which the sequence begins to repeat. For example, third cut tab stock has an order count of 3 (this is also sometimes called the modulus of the ordered media).

If the "media-order-count" is 1, then the media is not ordered.

The "media-order-count-supported" (rangeOfInteger(1:MAX)) Printer attribute identifies the range of values of this "media-order-count" member attribute that the Printer supports.

3.10.8 media-label-type (type3 keyword | name(MAX))

The "media-label-type" member attribute identifies the label characteristics of the media. The standard keyword values are:

'none'	The media MUST NOT be labeled stock.
'standard'	The media MUST be the site-defined standard labeled stock.

If this member attribute is supported, the Printer MUST support at least the 'none' and 'standard' values.

The "media-label-type-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute identifies the values of this "media-label-type" member attribute that the Printer supports, i.e., the label characteristics supported, which MUST include the 'none' keyword value so that validation follows the normal rules.

3.10.9 media-size (collection)

The "media-size" member attribute is a collection that explicitly specifies the numerical media width and height dimensions.

It is RECOMMENDED that a client localize the collection values to the size names that users are familiar with, such as 'letter' and 'A4', possibly also including the exact dimensions as well (and in the units appropriate for the user's locale). If a client does not recognize a pair of numbers as a named size, it can simply display the two numbers instead. Thus the pair of size dimensions serve the same function as keyword values, except that the client has an obvious fallback display for an unrecognized pair, namely, the actual dimension numbers.

The "media-size" collection member attributes are:

1052

Table 8 - "media-size" member attributes

Attribute name	attribute syntax	request	Printer Support
x-dimension	integer (0:MAX)	MUST	MUST
y-dimension	integer (0:MAX)	MUST	MUST

1053

1054

1055

1056

1057

1058

1059

1060

1061

1062

1063

1064

1065

1066

1067

1068

1069

1070

1071

1072

1073

1074

1075

1076

3.10.9.1 x-dimension (integer(0:MAX))

Indicates the size of the media in hundredths of a millimeter along the bottom edge of the media. See section 2.3 regarding the coordinate system. This unit is equivalent to 1/2540 th of an inch resolution.

3.10.9.2 y-dimension (integer(0:MAX))

Indicates the size of the media in hundredths of a millimeter along the left edge of the media. See section 2.3 regarding the coordinate system. This is equivalent to 1/2540 th of an inch resolution.

3.10.9.3 media-size-supported (1setOf collection)

Indicates the sizes supported by the Printer. A requested media size dimension matches a supported media dimension if it is within an implementation-defined tolerance. For example, PostScript [redbook] specifies a tolerance of 5 points (5/72 of an inch = 1.7 mm) of a supported dimension, i.e., within 176 units of the value of the dimension.

The "media-size-supported " collection member attributes are:

Table 9 - "media-size-supported" member attributes

Attribute name	attribute syntax	request	Printer Support
x-dimension	integer (0:MAX) rangeOfInteger (0:MAX)	MUST	MUST
y-dimension	integer (0:MAX) rangeOfInteger (0:MAX)	MUST	MUST

1077

1078

1079

1080

1081

1082

1083

1084

1085

3.10.9.3.1 x-dimension (integer(0:MAX) | rangeOfInteger(0:MAX))

Indicates the size of the media in hundredths of a millimeter along the bottom edge of the media. The rangeOfInteger attribute syntax accommodated variable size implementations, including web printers. See section 2.3 regarding the coordinate system. This is equivalent to 1/2540 th of an inch resolution.

3.10.9.3.2 y-dimension (integer(0:MAX) | rangeOfInteger(0:MAX))

Indicates the size of the media in hundredths of a millimeter along the left edge of the media. The rangeOfInteger attribute syntax accommodated variable size implementations, including web printers. See section 2.3 regarding the coordinate system. This is equivalent to 1/2540 th of an inch resolution.

3.10.10 media-weight-metric (integer(0:MAX))

The "media-weight" member attribute indicates the weight of the desired media rounded to the nearest whole number of grams per square meter. The "media-weight-supported" (1setOf integer(MAX)) Printer attribute identifies the values of this "media-weight" member attribute that the Printer supports, i.e., the weights supported in metric units.

3.10.11 media-weight-english (integer(0:MAX))

The "media-weight-english" member attribute indicates the weight of the desired media rounded to the nearest whole number of pounds.

If a Printer supports the "media-weight-english" member attribute, it **MUST** also support the "media-weight-metric" member attribute (but vice-versa is **OPTIONAL**). If the Printer supports both weight member attributes, the values **SHOULD** be available in both units for each medium. Then users can request media with either units.

Note: The use of pounds is actually pounds per ream. However, the size of a ream depends on the type of media. For example:

Bond paper	20 lb = 75 g/m**2	1 lb = 3.750 g/m**2
Index Bristol tab stock	90 lb = 163 g/m**2	1 lb = 1.811 g/m**2
Cover stock	65 lb = 176 g/m**2	1 lb = 2.708 g/m**2
Rank paper	55 lb = 80 g/m**2	1 lb = 1.455 g/m**2
Newsprint		1 lb = 1.627 g/m**2

Note: Even for bond paper, the conversion between the two units of measure is approximate in order to give integer values in both system of units.

The "media-weight-english-supported" (1setOf integer(0:MAX)) Printer attribute identifies the values of this "media-weight-english" member attribute that the Printer supports, i.e., the weights supported in English units.

3.10.12 media-front-coating (type3 keyword | name(MAX)) and media-back-coating (type3 keyword | name(MAX))

The "media-front-coating" and "media-back-coating" member attributes indicate what pre-process coating has been applied to the front and back of the desired media, respectively.

Standard keyword values for "media-front-coating" and "media-back-coating" are:

'none'	Indicated that the media MUST not have any coating.
'any'	Indicates that the media MUST be coated, but the specific coating type is not important.
'glossy'	Indicates that the media MUST have a "glossy" coating.
'high-gloss'	Indicates that the media MUST have a "high-gloss" coating.
'semi-gloss'	Indicates that the media MUST have a "semi-gloss" coating.
'satin'	Indicates that the media MUST have a "satin" coating.
'matte'	Indicates that the media MUST have a "matte" coating.

The "media-front-coating-supported" (1setOf (type3 keyword | name(MAX))) and "media-back-coating-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute identifies the values of these "media-front-coating" and "media-back-coating" member attributes that the Printer supports.

3.10.13 media-recycled (type3 keyword | name(MAX))

The "media-recycled" member attribute indicates the recycled characteristics of the media. The standard keyword values are:

'none'	The media MUST NOT be recycled.
'standard'	The media MUST be the site-defined standard recycled stock.

If this member attribute is supported, the Printer MUST support at least the 'none' and 'standard' values.

The "media-recycled-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute identifies the values of this "media-recycled" member attribute that the Printer supports, i.e., the recycled characteristics supported, which MUST include the 'none' keyword value so that validation follows the normal rules.

3.10.14 media-default (type3 keyword | name(MAX)) or media-col-default (collection)

The "media-default" (see [ipp-mod] section 4.2.11) or the "media-col-default" Printer attribute specifies the media that the Printer uses, if the client omits both the "media" and the "media-col" Job Template attributes in the Job Creation operation (and the PDL doesn't include a media specification). The member attributes are defined in Table 7. A Printer MUST support the same member attributes for this default collection attribute as it supports for the corresponding "media-col" Job Template attribute.

The "media-default" and "media-col-default" Printer attributes MUST both be configured to specify

the same media instance. If the administrator sets one of them to a value (either locally or with the Set-Printer-Attributes operation - see [ipp-set]), the Printer MUST set the other attribute's value to specify the same media instance or to the 'unknown' out-of-band value, if there isn't a corresponding value to be set for the other attribute. If a client attempts to set both attributes, but their values specify different media instances, the Printer MUST reject the Set-Printer-Attributes operation and return the 'client-error-conflicting-attributes' status code. The reason to have both default attributes configured, is so that clients that only know about the "media" attribute will see the "media-default" attribute, while clients that know about the "media-col" attribute will be able to determine the characteristics of the media default.

3.10.15 media-ready (1setOf (type3 keyword | name(MAX))) and media-col-ready (1setOf collection)

The "media-ready" (see [ipp-mod] section 4.2.11) and "media-col-ready" Printer attribute identifies the media that are available for use without human intervention, i.e., the media that are ready to be used without human intervention. The collection value MUST have all of the member attributes that are supported in Table 7. If this attribute is supported, the Printer MUST support the IPP/1.1 "media-ready" (1setOf (type3 keyword | name(MAX))) Printer attribute also. The i th value of the "media-ready" corresponds to the i th value of the "media-col-ready" attribute, so that the client can correlate the media name or keywords with the collection values, i.e., determine the characteristics of each ready media instance.

3.10.16 media-col-supported (1setOf type2 keyword)

The "media-col-supported" Printer attribute identifies the keyword names of the member attributes supported in the "media-col" collection Job Template attribute, i.e., the keyword names of the member attributes in Table 7 that the Printer supports.

3.11 page-delivery (type2 keyword)

This attribute indicates whether print-stream pages of the job are to be delivered to the output bin or finisher in the same page order as the original document, or, in reverse of that order, and, whether the print-stream pages are delivered face up or face down. The "page-delivery" attribute specifies the intent based on the "original document" page order. See section 2.4 for a complete discussion on the ordering of print-stream pages.

Standard keyword values for page delivery are:

'same-order-face-up'	The media sheets that represent the printed document MUST be delivered to the output bin or finishing device in the same order as defined by the "page-order-received" attribute. Further, side one of each sheet MUST be delivered face up to the output bin or finishing device.
----------------------	--

'same-order-face-down'	The media sheets that represent the printed document MUST be delivered to the output bin or finishing device in the same order as defined by the "page-order-received" attribute. Further, side one of each sheet MUST be delivered face down to the output bin or finishing device.
'reverse-order-face-up'	The media sheets that represent the printed document MUST be delivered to the output bin or finishing device in the reverse order by the "page-order-received" attribute. Further, side one of each sheet MUST be delivered face up to the output bin or finishing device.
'reverse-order-face-down'	The media sheets that represent the printed document MUST be delivered to the output bin or finishing device in the reverse order by the "page-order-received" attribute. Further, side one of each sheet MUST be delivered face down to the output bin or finishing device.
'system-specified'	The Printer selects the most efficient delivery order based on other Job Template attributes supplied by the client, such as "finishings" and "page-order-received".

1198
 1199
 1200
 1201
 1202
 1203
 1204
 1205
 1206
 1207

The "page-delivery" attribute is often used in conjunction with on-line and off-line finishing devices. The intent is to be able to deliver the media sheets in either the order of the page-stream pages as defined in the "original document" or in the reverse of that order.

3.11.1 Interaction with the "page-order-received" attribute

The "page-order-delivery" attribute is dependent on the value of the "page-order-received" attribute (defined in section 3.12 below):

"page-order-received"	"page-delivery"	Description of behavior
'1-to-n-order'	'same-order-face-up'	The first print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing up.
'1-to-n-order'	'same-face-order-down'	The first print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing down.
'1-to-n-order'	'reverse-order-face-up'	The last print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second to last "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing up.

'1-to-n-order'	'reverse-order-face-down'	The last print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second to last "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing down.
'n-to-1-order'	'same-order-face-up'	The first print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing up.
'n-to-1-order'	'same-order-face-down'	The first print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing down.
'n-to-1-order'	'reverse-order-face-up'	The last print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second to last "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing up.
'n-to-1-order'	'reverse-order-face-down'	The last print-stream page in the "document data" MUST be the first print-stream page delivered, followed by the second to last "print-stream" page, and so on. Further, each media sheet MUST be delivered with side one of the sheet facing down.

1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220

3.12 page-order-received (type2 keyword)

This attribute specifies the page order of the print-stream pages defined in the document data. The "page-order-received" attribute does not provide any direct processing instructions, it only provides information about the page order so that the client can specify ordinal page numbers with respect to the original source document, rather than having to take into account whether the print stream pages are being sent "one to N" or "N to one". For example, consider such Job Template attributes as "insert-sheet" (section 3.2) and "page-exceptions" (see [ipp-except]). See section 2.4 for a complete discussion of print-stream page order.

Standard keyword values for "page-order-received" are:

'1-to-n-order'	The print-stream pages defined in the document data are in the same order as the original document.
'n-to-1-order'	The print-stream pages defined in the document data are in the reverse order of the original document.

1221
1222
1223
1224
1225

The "page-order-received" attribute applies to all documents in a Job Creation or Document Creation request. If a job consists of multiple documents, and all of the documents are not in the same page order, either '1-to-n-order' or 'reverse,' then inconsistent processing of other Job Template attributes that depend on "page-order-received" may occur.

1226

1227

If the "page-order-received" attribute is not present in a Job Creation or Document Creation request, then the printer SHOULD assume a value of '1-to-n-order.'

1228

1229

1230

3.13 separator-sheets (collection)

1231

1232

This attribute specifies which separator sheets MUST be printed with the job. Separator sheets are used to separate individual copies of a multiple copy job (i.e., when the "copies" attribute is greater than 1). The "separator-sheets" attribute is dependent both on the value of "multiple-document-handling" and on the value of "sheet-collate" (see [ipp-prog]). See sections 2.2 and 3.13.1 for a detailed description and examples of what constitutes a "set."

1233

1234

Separator sheets may either be non-imaged sheets, or may contain Printer generated information.

1235

1236

The 'collection' attribute syntax allows a client to specify media for job separator sheets that is different than the current media being used for the print-stream page impressions. The collection consists of:

1237

1238

1239

1240

1241

1242

1243

1244

Table 10 - "separator-sheets" member attributes

Attribute name	attribute syntax	request	Printer Support
separator-sheets-type	type3 keyword name(MAX)	MUST	MUST
media	type3 keyword name(MAX)	MAY be neither or one of, but NOT both	MUST
media-col	collection		MAY

1245

1246

1247

3.13.1 separator-sheet-type (type3 keyword | name(MAX))

1248

1249

The "separator-sheets-type" member attribute specifies which separator sheets type the Printer MUST use for the separator sheets. Standard keyword values are:

1250

1251

'none'	No separator sheets are to be delivered with the printed output.
'slip-sheets'	A separator sheet MUST be printed between "sets" of the job.
'start-sheet'	A separator sheet MUST be printed to indicate the start of each "set" of the job.
'end-sheet'	A separator sheet MUST be printed to indicate the end of each "set" of the job.
'wrap-sheets'	Separator sheets MUST be printed to indicate both the start and end of each "set" of the job.

1252

1253

1254

1255

1256

Example: A job is created consisting of a single document, with the job template attribute "copies" equal to '10' and "separator-sheets-type" equal to 'slip-sheets'. If each of the 10 "sets" is denoted by (J1), (J2) ... (J10), and a separator sheet is denoted by S, then the delivered output would be: (J1) S (J2) S ... S (J9) S (J10).

1257
1258 The "separator-sheets-type-supported" (1setOf (type3 keyword | name(MAX))) Printer attribute
1259 identifies the values of this "separator-sheet-type" member attribute that the Printer supports, i.e.,
1260 the type names of the separator sheets.
1261

1262 **3.13.2 media (type3 keyword | name(MAX)) or media-col (collection)**

1263
1264 Either the "media" (defined in [ipp-mod] section 4.2.11) or the "media-col" member attribute is used
1265 to indicate the media that the Printer MUST use for the job separator sheet. The member attributes
1266 are the same as those for the "media-col" attribute shown in Table 7.
1267

1268 If the client omits both the "media" and the "media-col" member attributes, then the implementation
1269 selects a media instance (by means outside the scope of this document) that is appropriate for
1270 separator sheets. The client MUST NOT supply both the "media" and the "media-col" member
1271 attribute. If client supplies such a mal-formed request by supplying both, the Printer MUST
1272 (depending on implementation) either (1) reject the request and return the 'client-error-bad-request'
1273 status code (see [ipp-mod] section 13.1.4.1) or (2) use either the "media" or the "media-col" member
1274 attribute, independent of the value of the "ipp-attribute-fidelity" attribute supplied by the client.
1275

1276 Since this "media" member attribute has the same name as the "media" Job Template attribute
1277 defined in [ipp-mod] section 4.2.11), the "media-supported" (1setOf (type3 keyword | name(MAX)))
1278 Printer attribute (also defined in [ipp-mod] section 4.2.11) identifies the values of this "media"
1279 member attribute (as well as the values of the "media" Job Template attribute) that the Printer
1280 supports, i.e., the names of the supported media.
1281

1282 Since this "media-col" member attribute has the same name as the "media-col" Job Template
1283 attribute defined in section 3.10), the "media-col-supported" Printer attribute (defined in section
1284 3.10.16) identifies the keyword names of the member attributes supported in this "media-col"
1285 member attribute (as well as the keyword names of the "media-col" Job Template attribute), i.e., the
1286 names of the member attributes in Table 7 that the Printer supports.
1287

1288 **3.13.3 separator-sheets-default (collection)**

1289
1290 The "separator-sheets-default" Printer attributes specify the separator sheets that the Printer MUST
1291 provide, if any, if the client omits the "separator-sheets" Job Template attribute. The member
1292 attributes are defined in Table 10. A Printer MUST support the same member attributes for this
1293 default collection attribute as it supports for the corresponding "separator-sheets" Job Template
1294 attribute.
1295
1296

1297 **3.13.4 separator-sheets-supported (1setOf type2 keyword)**

1298
1299 The "separator-sheets-supported" attribute identifies the keyword names of the member attributes
1300 supported in the "separator-sheets" collection Job Template attribute, i.e., the names of the member
1301 attributes in Table 10 that the Printer supports.

1302

1303 3.14 Impression Image Shifting Attributes

1304

1305 The attributes defined in this sub-section shift the impression images as specified in the attribute definition.
1306 The Printer MUST apply this shifting to the resulting impression after creating a single impression from a
1307 number of page images as specified by either (1) the "number-up" attribute (see [ipp-mod] sections 4.2.9
1308 and 15.3) or any other attribute that specifies imposition. In other words, these attributes affect the
1309 impression, not individual page images.

1310

1311 3.14.1 x-image-auto-center (boolean)

1312


1313 This attribute causes the impression to be centered along the x-axis on the media to which it is applied.

1314

1315 If the "x-image-shift," "x-side1-image-shift" or "x-side2-image-shift" attributes are specified, then the
1316 printer MUST apply the "x-image-auto-center" attribute first, followed by the "x-image-shift" attribute, and
1317 finally the "x-side1-image-shift" and "x-side2-image-shift" attributes.

1318

1319 For example, if the print-stream image normally is placed on the media sheet as follows:




1320

1321

1322 with "x-image-auto-center" = 'true' (1), the result would be:

1323



1324

1325

1326 3.14.2 x-image-shift (integer(MIN:MAX))

1327

1328 This attribute causes the impression on both sides of each sheet, to be shifted in position with respect to the
1329 media on which the impression is to be rendered. The direction of shift **MUST** be along the x-axis of the
1330 Coordinate System (see section 2.3) with respect to the medium. The sign of the value indicates the
1331 direction of the shift.
1332

1333 If the client supplies the "x-image-auto-center," "x-side1-image-shift" or "x-side2-image-shift" attributes,
1334 then the Printer **MUST** apply the "x-image-auto-center" attribute first, followed by the "x-image-shift"
1335 attribute, and finally the "x-side1-image-shift" and "x-side2-image-shift" attributes.
1336

1337 The unit of measure for this attribute is hundredths of a millimeter. This is equivalent to 1/2540th of an inch
1338 resolution.
1339

1340 **3.14.3 x-side1-image-shift (integer(MIN:MAX))**

1341
1342
1343 This attribute causes the impression, on the front of each sheet, to be shifted in position with respect to the
1344 media on which the impression is to be rendered. The direction **MUST** be along the x-axis of the
1345 Coordinate System (see section 2.3) with respect to the medium. The sign of the value indicates the
1346 direction of the shift.
1347

1348 If the bind edge is along the y-axis, then a bind edge image shift can be accomplished by applying
1349 impression shifts of equal magnitude, and opposite sign, to the "x-side1-image-shift" and "x-side2-image-
1350 shift" attributes, respectively (assuming that the "sides" attribute is 'two-sided-long-edge').
1351

1352 If the client supplies the "x-image-auto-center" or "x-image-shift" attributes, then the Printer **MUST** apply
1353 the "x-image-auto-center" attribute first, followed by the "x-image-shift" attribute, and finally the "x-side1-
1354 image-shift" and "x-side2-image-shift" attributes.
1355

1356 The unit of measure for this attribute is hundredths of a millimeter. This is equivalent to 1/2540th of an inch
1357 resolution.
1358

1359 **3.14.4 x-side2-image-shift (integer(MIN:MAX))**

1360
1361 This attribute causes the impression, on the back of each sheet, to be shifted in position with respect to the
1362 media on which the impression is to be rendered. The direction of shift **MUST** be along the x-axis of the
1363 Coordinate System (see section 2.3) with respect to the medium. The sign of the value indicates the
1364 direction of the shift.
1365

1366 If the bind edge is along the y-axis, then a bind edge image shift can be accomplished by applying
1367 impression shifts of equal magnitude, and opposite sign, to the "x-side1-image-shift" and "x-side2-image-
1368 shift" attributes, respectively (assuming that the "sides" attribute is 'two-sided-long-edge').
1369

1370 If the client supplies the "x-image-auto-center" or "x-image-shift" attributes, then the Printer **MUST** apply
1371 the "x-image-auto-center" attribute first, followed by the "x-image-shift" attribute, and finally the "x-side1-
1372 image-shift" and "x-side2-image-shift" attributes.

1373
1374 The unit of measure for this attribute is hundredths of a millimeter. This is equivalent to 1/2540th of an inch
1375 resolution.
1376

1377 1378 **3.14.5 y-image-auto-center (boolean)** 1379

1380 This attribute causes the impression to be centered along the y-axis on the media to which it is applied.
1381

1382 If the client supplies the "y-image-image," "y-side1-image-shift" or "y-side2-image-shift" attributes, then
1383 the Printer MUST apply the "y-image-auto-center" attribute first, followed by the "y-image-shift" attribute,
1384 and finally the "y-side1-image-shift" and "y-side2-image-shift" attributes.
1385

1386 1387 **3.14.6 y-image-shift (integer(MIN:MAX))** 1388

1389 This attribute causes the impression on both sides of each sheet, to be shifted in position with respect to the
1390 media on which the impression is to be rendered. The direction of shift MUST be along the y-axis of the
1391 Coordinate System (see section 2.3) with respect to the medium. The sign of the value indicates the
1392 direction of the shift.
1393

1394 If the client supplies the "y-image-auto-center," "y-side1-image-shift" or "y-side2-image-shift" attributes,
1395 then the Printer MUST apply the "y-image-auto-center" attribute first, followed by the "y-image-shift"
1396 attribute, and finally the "y-side1-image-shift" and "y-side2-image-shift" attributes.
1397

1398 The unit of measure for this attribute is hundredths of a millimeter. This is equivalent to 1/2540th of an inch
1399 resolution.
1400

1401 1402 **3.14.7 y-side1-image-shift (integer(MIN:MAX))** 1403

1404 This attribute causes the impression, on the front of each sheet, to be shifted in position with respect to the
1405 media on which the impression is to be rendered. The direction of shift MUST be along the y-axis of the
1406 Coordinate System (see section 2.3) with respect to the medium. The sign of the value indicates the
1407 direction of the shift.
1408

1409 If the bind edge is along the x-axis, then a bind edge image shift can be accomplished by applying
1410 impression shifts of equal magnitude, and opposite sign, to the "y-side1-image-shift" and "y-side2-image-
1411 shift" attributes, respectively (assuming that the "sides" attribute is 'two-sided-short-edge').
1412

1413 If the client supplies the "y-image-auto-center" or "y-image-shift" attributes, then the Printer MUST apply
1414 the "y-image-auto-center" attribute first, followed by the "y-image-shift" attribute, and finally the "y-side1-
1415 image-shift" and "y-side2-image-shift" attributes.
1416

1417 The unit of measure for this attribute is hundredths of a millimeter. This is equivalent to 1/2540th of an inch

1418 resolution.

1421 **3.14.8 y-side2-image-shift (integer(MIN:MAX))**

1423 This attribute causes the impression, on the back of each sheet, to be shifted in position with respect to the
1424 media on which the impression is to be rendered. The direction of shift **MUST** be along the y-axis of the
1425 reference coordinate system with respect to the medium. The sign of the value indicates the direction of the
1426 shift.

1428 If the bind edge is along the x-axis, then bind edge image shift can be accomplished by applying impression
1429 shifts of equal magnitude, and opposite sign, to the "y-side1-image-shift" and "y-side2-image-shift"
1430 attributes, respectively (assuming that the "sides" attribute is 'two-sided-short-edge').

1432 If the client supplies the "y-image-auto-center" or "y-image-shift" attributes, then the Printer **MUST** apply
1433 the "y-image-auto-center" attribute first, followed by the "y-image-shift" attribute, and finally the "y-side1-
1434 image-shift" and "y-side2-image-shift" attributes.

1436 The unit of measure for this attribute is hundredths of a millimeter. This is equivalent to 1/2540th of an inch
1437 resolution.

1439 **3.15 Usage in Document-Exceptions and Page-Exceptions**

1441 Most of the Job Template attributes defined in this document are defined for use in the "document-
1442 exceptions" (collection) and/or "page-exceptions" (collection) Job Template attributes (see [ipp-except]).
1443 According to that document, any Job Template attribute document **MUST** indicate the syntax and semantics
1444 for applying each Job Template attribute in any Document and/or Page exceptions.

1446 Table 12 augments the definitions of each Job Template attribute defined in this document by indicating
1447 with which parts of a job, the attribute "associates with" and "affects" (see [ipp-except]). All Job Template
1448 attributes associate with the Job, so that is not indicated in Table 12. A subset of the Job Template
1449 attributes are defined to be used in Document-Exceptions to affect Input-Document and are associated with
1450 Input-Documents only via the "document-exceptions" attribute. Another subset affect Output-Documents
1451 and are associated with either Input-Documents or Output-Document via the "document-exceptions"
1452 attribute. A final subset of Job Template attributes affects Sheets, Pages, or Impressions and are associated
1453 with Pages of an Input-Document or an Output-Document by the "pages-exceptions" attribute or associated
1454 with Input-Document or Output-Document via a "document-exceptions" attribute. See [ipp-except] for the
1455 syntax of the "document-exceptions" (1setOf collection), "page-exceptions" (1setOf collection) and "page-
1456 per-subset" (1setOf integer(1:MAX)) and semantics of association with Document-Exceptions, Page-
1457 Exceptions, Sheets, and Pages. The "pages-per-subset" attribute defines Output-Document to be subsets of
1458 pages within Input-Documents.

1460 Table 11 lists the possible attribute exception semantics for Job Template attributes and shows what clients
1461 can supply in Job Creation operations.

1462

Table 11 - Job Template Attribute Exception Semantics

Affects	Associates With	Exception attribute	member attributes
Job	Job	none	
Input-Document	Input-Document	"document-exceptions"	"input-documents"
Output-Document	Output-Document	"document-exceptions"	"output-documents"
		"pages-per-subset"	N/A
sheet, impression	Input-Document	"document-exceptions"	"input-documents"
	Output-Page	"page-exceptions"	"output-documents", "pages"
	Input-Page	"page-exceptions"	"input-documents", "pages"
	Output-Document	"document-exceptions"	"output-documents"
"pages-per-subset"		N/A	
Input-Document	"document-exceptions"	"input-documents"	

1463

1464

1465

1466

1467

1468

1469

1470

1471

1472

A client MUST NOT submit and a Printer MUST NOT support a Job Creation request with "document-exceptions" (collection), "page-exceptions" (collection), or "pages-per-subset" containing member attributes not indicated in Table 11 depending on what the Job Template attribute is defined to affect as indicated in Table 12. If a client submits a Job Creation request with such a member attribute and "ipp-attribute-fidelity" = 'true', the Printer MUST reject the request and return the 'client-error-bad-request' status code. If a client submits a Job Creation request with such a member attribute and "ipp-attribute-fidelity" = 'false' or omitted, the Printer MUST accept the request and return the 'successful-ok-ignored-or-substituted-attributes' status code, along with the collection and only those member attributes.

1473

Table 12 - Document and Page Exception Semantics by Attribute

Section or Attribute	Affects:
3.1 cover-front (collection) and cover-back (collection)	Output-Documents
3.2 insert-sheet (1setOf collection)	Output-Documents
3.3 job-account-id (name (MAX))	Job
3.4 job-accounting-sheets (collection)	Job
3.5 job-error-sheet (collection)	Job
3.6 job-message-to-operator (text(MAX))	Job
3.7 job-recipient-name (name(MAX))	Job
3.8 job-sheets-col (collection) - augments IPP/1.1 "job-sheets"	Job
3.9 job-sheet-message (text(MAX))	Job
3.10 media-col (collection) - augments IPP/1.1 "media"	Sheets
3.11 page-delivery (type2 keyword)	Output-Documents
3.12 page-order-received (type2 keyword)	Input-Documents
3.13 separator-sheets (collection)	Job
3.14.1 x-image-auto-center (boolean) through 3.14.8 y-side2-image-shift (integer(MIN:MAX))	Impressions

1474

4 Job Description Attributes

This section defines Job Description attributes for use with IPP/1.0 [RFC 2566] and IPP/1.1 [ipp-mod].

4.1 current-page-order (type2 keyword)

This attribute represents the current page order of the document data supplied with the job. Initially "current-page-order" is set to the value of the Job Template attribute "page-order-received." The value of "current-page-order" may change based on processing and the value of the "page-order-delivery" attribute. If the Printer changes the value of a Job's "current-page-order" Job Description attribute, then it is assumed that the associated document data has been transformed in some way to reflect this change. It should be noted that the document data that "current-page-order" refers to is not always the document data sent with the create request, but may also refer to the processed images that are to be delivered to the printer. The standard values for this attribute are the same as for of the "page-order-received" attribute (see section 3.12), namely '1-to-n-order' and 'n-to-1-order'.

5 Printer Description Attributes

This section defines Printer Description attributes for use with IPP/1.0 [RFC 2566] and IPP/1.1 [ipp-mod].

5.1 user-defined-names-supported (1setOf type2 keyword)

This Printer attribute identifies the "xxx" Job Template attributes that the Printer will accept user-defined name in a Job Creation request, i.e., a name that a client supplies that is not in the corresponding "xxx-supported" Printer attribute. In effect, the presence of the 'xxx' keyword value in this attribute suspends validation of the "xxx" attribute for any 'name' values supplied by the client. Thus a user can supply a custom name for this "xxx" attribute. If there are no Job Template attributes that will accept any name value, the value of this attribute MUST be the keyword 'none'.

For any "xxx" Job Template attributes identified by this attribute, the Printer suspends validation for values of type 'name' and the job is created containing the user-defined value, even when the client supplied the "ipp-attribute-fidelity" with a 'true' value (which would otherwise, have caused the Printer to reject the request, if the "xxx" value had not been among those of the Printer's "xxx-supported" attribute).

For example, the system administrator could add the 'media' keyword attribute name value to the "user-defined-names-supported" Printer attribute in order to allow the user to supply any media name value for the "media" attribute even if that name wasn't one of the media names in the Printer's "media-supported" attribute.

When the client supplies a 'yyy' value for the "xxx" attribute that is not in the "xxx-supported" Printer attribute, the Printer does not return the "xxx" value in the Unsupported Attributes group in the response. Instead, the Printer stores the requested attribute and value unmodified on the Job object for subsequent queries as with any supported value. Subsequently, a user or operator can query the Job using the Get-Job-

Attributes or Get-Jobs operations to see what user-defined value was requested. Depending on implementation and/or site policy, the Printer schedules the job following one of the following options:

1. Add the 'resources-are-not-supported' value (see section 6.1) to the Job's "job-state-reasons" attribute and move the job to the 'pending-held' state until either the operator adds the requested value to the Printer's "xxx-supported" attribute or the user or operator modifies the job to contain a value that is in the Printer's "xxx-supported" attribute; then releases the job using the Release-Job operation (see [ipp-mod] section 3.3.6).
2. Add the 'resources-are-not-supported' value to the Job's "job-state-reasons" attribute but keep the job in the 'pending' state and start to process the job as if the requested media were ready, but stop the job ("job-state" = 'processing-stopped') and the Printer ("printer-state" = 'stopped') and request immediate operator intervention. The operator loads the requested media and continues the Printer, using the Resume-Printer operation (see [ipp-mod] section 3.2.8).

6 Additional Values for Existing Attributes

This section defines additional values for existing attributes.

6.1 Additional values for the "job-state-reasons" Job attribute

This section defines additional values for the "job-state-reasons" (1setOf type2 keyword) Job Description attribute (see [ipp-mod] section 4.3.8):

'resources-are-not-supported': At least one of the resources needed by the job, such as media, fonts, resource objects, etc., is not supported on any of the physical printer's for which the job is a candidate. This condition MAY be detected when the job is accepted, or subsequently while the job is pending or processing, depending on implementation. The job may (1) remain in its current state, (2) be moved to the 'pending-held' state, depending on implementation and/or job scheduling policy, or (3) scheduled normally, but the Printer is put into the 'stopped' state when the job is attempted to be processed on the Printer. This value is intended for use with an implementation that supports the "user-defined-names-supported" Printer attribute (see section 5.1) which allows a job to be accepted with an unsupported 'name' value.

6.2 Additional values for the IPP/1.1 "job-sheets" Job Template Attribute

The following additional values are defined for the IPP/1.1 "job-sheets" Job Template attribute:

job-start-sheet	A job sheet MUST be printed to indicate the start of the job.
job-end-sheet	A job sheet MUST be printed to indicate the end of the job.
job-wrap-sheets	Job sheets MUST be printed to indicate the start and end of all the output associated with the job.

first-print-stream-page	Some users have customized the banner sheets in their environment (Microsoft, Novell, etc.) and prefer them instead of the printer's standard ones. The custom banner sheet is the first page of the PDL. When the client supplies the 'first-print-stream-page' value, the first page in the document data is printed as the job sheet and the printer's standard job sheet is suppressed.
-------------------------	---

1558
1559

6.3 Additional values for the IPP/1.1 "media" and "media-description" attributes

1560
1561

This section defines additional values for the "media" (type3 keyword | name(MAX)) Job Template attribute (see [ipp-mod] section 4.2.11), the "media" member attribute defined in this document in a number of the collection attributes, and the "media-description" member attribute defined in section 3.10.1:

1562
1563
1564
1565

If the Printer implementation supports the use of tray name keywords to identify media, there SHOULD be one and only one keyword assigned for each input tray on the printer. If multiple keywords for the same tray exist in "media-supported", the client UI could potentially become very confusing to the user because the Printer would appear to have more input trays than it actually has. However, see the discussion in the Printer MIB [RFC1759] about a manual input tray that uses the same input slot as a regular input tray. Also, if using tray names, it is RECOMMENDED that the printer implementation use the most descriptive keyword for a logical tray in order to assist the user or operator to recognize the matching physical tray at the printer. There are three methods to choose the keyword: 1) If the printer trays aren't physically labeled, the keyword SHOULD best match the physical location of the tray (e.g. 'top', 'bottom'). 2) If the printer trays are physically labeled, the keyword SHOULD best match the label of the tray (e.g. 'tray-1', 'tray-2'), 3) If more than one keyword matches the label of the tray, the keyword SHOULD be used that best distinguishes the tray from the Printer's other trays.

1566
1567
1568
1569
1570

If a Printer allows the media to be specified by tray name keyword, the Printer implementation MUST NOT use the 'name(MAX)' attribute syntax to create custom tray names, but rather MUST use the most appropriate tray name keyword value. This ensures interoperability among clients that submit jobs to multiple types of printers.

1571
1572
1573
1574
1575
1576
1577
1578

These are additional standard keyword values defined for input-trays.

1579
1580
1581
1582
1583
1584
1585

'bypass-tray'	The specified tray is used for handling odd or special paper. This paper tray usually has a small capacity and is physically located such that the paper travels through a shorter paper path. In some printer implementations, the 'bypass-tray' may also be used to bypass any marking device and be used for insert sheets. See the "insert-sheet" definition in section 3.2.
---------------	--

'tray-N'	The input tray that is best specified as a tray with values 'tray-1', 'tray-2'.... The correspondence between the 'tray-N' keyword and the actual input-tray is implementation dependent, as is the number of input trays. If this group of 'tray-N' values is supported, at least the 'tray-1' value MUST be supported.
----------	--

1586
1587
1588
1589
1590
1591

These are additional standard keyword values which are used by the implementation for specifying a pre-defined media size:

'iso-a4-wide'	Specifies the iso A4 cover size: 223 mm x 297 mm
'na-letter-cover'	Specifies the letter cover size: 9 in x 11 in
'jp-reply-postcard'	Specifies the Ofuku-Hagaki postcard size: 148 mm x 200 mm
'na-postcard'	Specifies the North American postcard size: 4.5 in x 6 in
'na-8x10'	Specifies the 8x10 size.
'na-5x7'	Specifies the 5x7 size.
'taiwan-815'	Specifies the 815 Taiwan size: 267 mm x 388 mm
'iso-220x330'	Specifies the 220 mm x 330 mm size

1592
1593

7 Conformance Requirements

1594
1595

This section summarizes the Conformance Requirements detailed in the definitions in this document for clients and Printer objects (servers or devices).

1598

7.1 Conformance Requirements for Printer objects

1599
1600

In general each of the attributes defined in this document are OPTIONAL for a Printer to support, so that Printer implementers MAY implement any combination of attributes. Only the following conditional conformance requirements are defined:

1601
1602
1603
1604

If the Printer supports:	then the Printer MUST also support (but vice-versa is OPTIONAL):
"cover-back"	"cover-front"
"job-sheets-col"	"job-sheets" (see [ipp-mod] section 4.2.3)
"media-col"	"media" (see [ipp-mod] section 4.2.11)
"media-col-ready"	"media-ready" (see [ipp-mod] section 4.2.11)
"x-side2-image-shift"	"x-side1-image-shift"
"y-side2-image-shift"	"y-side1-image-shift"
"x-side1-image-shift"	"x-image-shift"

"y-side1-image-shift"

"y-image-shift"

1605
1606 Each of the collection attribute definitions indicate which member attributes are REQUIRED and which are
1607 OPTIONAL for a Printer to support and is not repeated here.
1608

1609 If a Printer supports the 'collection' attribute syntax of a Job Template attribute , then it MUST support the
1610 distinguished none value defined for that collection. See section 2.6.
1611

1612 Support of the 'name' attribute syntax for Job Template attributes and collection member attributes is
1613 OPTIONAL, as in IPP/1.1.
1614
1615

1616 **7.2 Conformance Requirements for clients**

1617

1618 Clients that support two Job Template attributes that control the same aspect, such as "media" and "media-
1619 col", MUST NOT supply both in a Job Creation request as indicated in the definitions of these attributes.
1620

1621 Clients that support a "xxx" collection Job Template attribute SHOULD use the Get-Printer-Attributes
1622 request to obtain the "xxx-default" collection and display that to the user, so that the user can make any
1623 changes before submitting the Job. Then the client submits values for all member attributes, rather than
1624 depending on the Printer's defaulting for omitted member attributes, since such defaulting is
1625 implementation dependent and will vary from Printer to Printer.
1626

1627 **8 IANA Considerations**

1628

1629 IANA will be called on to register the attributes defined in this document, using the procedures outlined in
1630 [ipp-mod] section 6.
1631
1632

1633 **9 Internationalization Considerations**

1634

1635 The IPP extensions defined in this document require the same internationalization considerations as any of
1636 the Job Template attributes defined in IPP/1.1 [ipp-mod].
1637
1638

1639 **10 Security Considerations**

1640

1641 The IPP extensions defined in this document require the same security considerations as any of the Job
1642 Template attributes defined in IPP/1.1 [ipp-mod].
1643
1644

11 References

[ipp-coll]

deBry, R., , Hastings, T., Herriot, R., "Internet Printing Protocol/1.0 & 1.1: collection attribute syntax", <draft-ietf-ipp-collection-00.doc>, work in progress, September 9, 1999.

[ipp-except]

Ocke, K., Herriot, R., "Internet Printing Protocol (IPP): Exception Attributes for Documents and Pages", <pwg-ipp-exceptions-model-000131.doc>, work in progress, January 31, 2000.

[ipp-prog]

Hastings, T., Bergman, R., Lewis, H., "Proposed Job Progress Attributes for IPP", <draft-ietf-ipp-job-prog.txt> work in progress, February 2, 2000.

[ipp-mod]

deBry, R., , Hastings, T., Herriot, R., Isaacson, S., Powell, P., "Internet Printing Protocol/1.1: Model and Semantics", < draft-ietf-ipp-model-v11-04.txt>, work in progress, June 23, 1999.

[ipp-pro]

Herriot, R., Butler, S., Moore, P., Tuner, R., "Internet Printing Protocol/1.1: Encoding and Transport", <draft-ietf-ipp-protocol-v11-03.txt>, work in progress, June, 1999.

[redbook]

"PostScript(R) LANGUAGE REFERENCE, third edition", Adobe Systems Incorporated, February 1999.

[RFC1759]

Smith, R., Wright, F., Hastings, T., Zilles, S., and Gyllenskog, J., "Printer MIB", RFC 1759, March 1995.

[RFC2119]

S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", RFC 2119 , March 1997

[RFC2566]

deBry, R., , Hastings, T., Herriot, R., Isaacson, S., Powell, P., "Internet Printing Protocol/1.0: Model and Semantics", RFC 2566, April 1999.

12 Author's Addresses

Kirk Ocke
Xerox Corporation
800 Phillips Road
Webster, NY 14580

1681 Phone: 716 422-4832
1682 e-mail: Kirk.Ocke@usa.xerox.com

1683
1684 Tom Hastings
1685 Xerox Corporation
1686 737 Hawaii St. ESAE 231
1687 El Segundo, CA 90245

1688
1689 Phone: 310-333-6413
1690 Fax: 310-333-5514
1691 e-mail: hastings@cp10.es.xerox.com
1692
1693

1694 **13 Appendix A: Change History**

1695
1696 This section summarizes the changes to the document. Each sub-section is in reverse chronological order.
1697 Adding or removing ISSUES that don't change the document are not listed here.
1698
1699

1700 **13.1 Changes to the May 9, 2000 to create the June 5, 2000 version**

1701
1702 The following changes were made to the May 9, 2000 version to create the June 5, 2000 version:
1703

- 1704 1. Added the "cover-type-supported" Printer attribute.
- 1705
1706 2. REQUIRED (rather than RECOMMENDED) the Printer to make the "job-sheets-default" and "job-
1707 sheets-col-default" Printer attributes identify the same job sheet instance or have one of them set to the
1708 'unknown' out-of-band value.
- 1709
1710 3. REQUIRED (rather than RECOMMENDED) the Printer to make the "media-default" and "media-col-
1711 default" Printer attributes identify the same media instance or have one of them set to the 'unknown' out-
1712 of-band value.
- 1713
1714 4. Added the 'system-specified' keyword value to the "page-delivery" Job Template attribute.

1717 **13.2 Changes to the April 26, 2000 to create the May 9, 2000 version**

1718
1719 The following changes were made to the April 26, 2000 version to create the May 9, 2000 version:
1720

- 1721 1. Clarified that both the "job-sheets-default" and "job-sheets-col-default" Printer attributes SHOULD both
1722 be configured to specify the same job-sheet instance.
- 1723 2. Changed the "media-description" member attribute back to 'type3 keyword | name(MAX)' from 'text' so
1724 that clients can localize the value and the "media-description-supported" back to '1setOf (type3 keyword

- 1725 | name(MAX) from 'integer(0:255)'.
 1726 3. Deleted the "media-weight-type" attribute - don't have two ways to specify the same thing until there is
 1727 a way to indicate which one the Printer supports.
 1728 4. Replaced the "media-weight" and "media-weight-units" with "media-weight-metric" and "media-
 1729 weight-english", so that implementations can support "media-weight-metric" only or both and clients
 1730 can request either.
 1731 5. Clarified that the "media-size" tolerance is implementation-defined. The 5 points tolerance for
 1732 PostScript is given as an example.
 1733 6. Removed "-supported" from the "x-dimension" and "y-dimension" member attributes to agree with the
 1734 collection specification.
 1735 7. Clarified that both the "media-default" and "media-col-default" Printer attributes SHOULD both be
 1736 configured to specify the same media instance.
 1737 8. Changed "job-separator-sheets" collection attribute so that if the client supplies neither the "media" or
 1738 the "media-col" member attributes, the implementation picks some appropriate separator sheet medium,
 1739 rather than using the document's media.
 1740 9. Added the 'first-print-stream-page' keyword value to the "job-sheets" Job Template attribute.
 1741

1742 **13.3 Changes to the April 11, 2000 to create the April 26, 2000 version**

1743
 1744 The following changes were made to the April 11, 2000 version to create the April 26, 2000 version:
 1745

- 1746 1. Added discussion about distinguished none values for all but a few Job Template attributes.
 1747 2. Clarified the table and language for collections that have both "media" and "media-col" around the
 1748 client sending neither (error for some collection attributes, not for others), one or the other, or both
 1749 (error).
 1750 3. Removed the use of the 'none' out-of-band value and defined distinguished values for keywords (usually
 1751 'none', or 'no-xxx'), strings (zero-length), and integers (usually 0) instead. Existing clients and Printers
 1752 might get confused with the (new) 'none' out-of-band value.
 1753 4. Broke "job-error-sheet-type" into two member attributes: "job-error-sheet-type" and "job-error-sheet-
 1754 when".
 1755 5. Removed the "s" from "job-error-sheet".
 1756 6. Banned "media-default" and "media-col-default" from both having a value, even if one is the name of
 1757 the other. Required the Printer to set the other to 'no-value' out-of-band value.
 1758 7. Added "media-label-type" (type3 keyword | name(MAX)), and "media-recycled" (type3 keyword |
 1759 name(MAX)) member attributes to "media-col".
 1760 8. Changed the "xxx-supported" (boolean) to "xxx-supported" (integer(0:X) so that the maximum length
 1761 of the string could be queried by the client.
 1762 9. Added 'gray', 'ivory', and 'orange' colors
 1763 10. Changed media-pre-printed (boolean) to media-pre-printed (type3 keyword | name(MAX)) and defined
 1764 'blank', 'pre-printed', and 'letter-head'.
 1765 11. Removed -supported from the member attributes of the "media-col-supported" (1setOf collection).
 1766 12. Added 'none' keyword value to media-front-coating (type3 keyword | name(MAX)) and media-back-
 1767 coating (type3 keyword | name(MAX))
 1768 13. Replaced the 'user-define' and 'user-define-supported' out-of-band values with the "user-defined-names-
 1769 supported" Printer attribute. This will help existing clients that query the Printer.

1770 14. Added some "media" keyword values.

1771 15. Enhanced the Conformance Section with client requirements.

1773 **13.4 Changes to the February 7, 2000 to create the April 11, 2000 version**

1774
1775 The following changes were made to the February 7, 2000 version to create the April 11, 2000 version:

- 1776
1777 1. Clarified that the "page-ranges" Job Template attribute does not affect the print-stream page numbering.
- 1778
1779 2. Aligned the collection attribute definitions to agree with the updated Collection [ipp-coll] document:
 - 1780 a) Changed "xxx-supported"(boolean) to "xxx-supported" (1setOf type2 keyword) to return the keyword names of the member attributes.
 - 1781 b) Removed the 'type3 keyword | name' attribute syntaxes from "xxx" (type3 keyword | name | collection) attributes and moved those values into a new "xxx-type" member attribute in the collection for new attributes. For the existing IPP/1.1 "job-sheets" (type3 keyword | name) and "media" (type3 keyword | name) attributes created new "xxx-col" (collection) companion attributes.
 - 1782 c) For each collection attribute that had a "media" (type3 keyword | name(MAX) | collection) member attribute, removed the 'collection' and added a new OPTIONAL "media-col" (collection) member attribute to carry the media characteristics.
 - 1783 d) Clarified that a client MUST NOT supply both "media" and a "media-col" Job Template attributes or member attributes. If a Printer receives such a bad request, it MUST either reject it or use one or the other attributes depending on implementation.
 - 1784 e) Add prefix names to member attributes when they are intended to be unique, such as "cover-" to "cover-printed-sided" so that the "xxx-supported" would not be ambiguous. Same for "insert-" to "insert-after-page-number" and "insert-count".
 - 1785 f) Added "xxx-default" (collection) for all collection attributes for consistency as required by [ipp-coll].
 - 1786 g) Added "xxx-supported" Printer attributes for all member attributes for consistency as required by [ipp-coll].
- 1787
1788 3. Removed the prefix from the "media" and the "media-col" member attributes, so that they are the same as the IPP/1.1 Job Template attributes.
- 1789
1800 4. Added the insert-after-page-number-supported" (1setOf type2 keyword) Printer attribute for consistency.
- 1801
1802 5. Added that a value of MAX for "insert-after-page-number" inserts a page after the last page in the document no matter how many pages are in the document.
- 1803
1804 6. Changed "insert-sheet" to agree with the Exceptions document [ipp-except], so that if a page number is not the first on a sheet, the insert happens after that sheet, and the page is forced to the next sheet and a warning given using the "job-warnings-count" Job Description attribute and the Job's 'job-warnings-detected' job-state-reasons.
- 1805
1806 7. Add the "insert-count-supported (integer(1:MAX)) Printer attribute for consistency.
- 1807
1808 8. Clarified that the "media" attribute maps a name or keyword to a media instance, but that not all media instances need have an associated media name or keyword. Also that no two media instances can have the same "media" attribute name or keyword.
- 1809
1810 9. Clarified that that the "media-col" collection attribute maps a set of characteristics to a media instance

- 1815 and that all media instances must have a distinct set of characteristics, not counting their names. The
1816 "media-description" member attribute can be used as a characteristics to distinguish two otherwise
1817 identical media instances.
- 1818 10. Changed the name of the "media-name" member attribute to "media-description" and its attribute
1819 syntax from 'type3 keyword | name(MAX)' to 'text(255)' to make sure that the value is just an
1820 arbitrary string with no semantic content, such as a tray name or size.
 - 1821 11. Clarified that several media instances can have the same "media-description" member attribute value.
 - 1822 12. Specified the tolerance for media size matching of 5 points, same as PostScript.
 - 1823 13. Removed the type3 keyword from the "media-size" (collection) member attribute, so as to have only
1824 one way to specify size, namely a pair of integers. The client can use these integers to map to a media
1825 size name in the locale of the user, similar to keywords.
 - 1826 14. Added a rangeOfInteger to the "media-size-supported" (1setOf collection) member attributes and so
1827 added a "-supported" suffix to "x-dimension" and "y-dimension" member attributes since they now
1828 have different attribute syntaxes to the member attributes of the "media-size" member attribute.
 - 1829 15. Added "media-col-ready" (1setOf collection) Job Template Printer attribute to show the
1830 characteristics of the ready media.
 - 1831 16. Clarified that the IPP/1.1 "media-ready" (1setOf (type3 keyword | name(MAX))) Printer attribute
1832 MUST also be supported, and that the values correspond, so that the client can determine the
1833 mapping of the media names/keywords to the media characteristics for the ready media at least.
 - 1834 17. Deleted "sheet-collate", since it is already defined in the "Job Progress Attributes" document [ipp-
1835 prog].
 - 1836 18. Added the section on Document and Page Exceptions to indicate the semantics of each Job Template
1837 attribute as required by [ipp-except].
 - 1838 19. Deleted the definition of the 'none' out-of-band attribute value, since it is defined in the [ipp-coll]
1839 document.
 - 1840 20. Added the 'user-define' out-of-band attribute value for use as one of the values of the Printer's "xxx-
1841 supported" attributes to indicate that a client can supply a name that is not in the Printer's supported
1842 list, i.e., can supply custom names.
 - 1843 21. Added the 'user-define-supported' out-of-band value so that an implementation can indicate in the
1844 "xxx-supported" returned by the Get-Printer-Supported-Values operation whether or not it will allow
1845 the administrator to set the 'user-define' out-of-band value in the corresponding Printer's "xxx-
1846 supported" attribute.
 - 1847 22. Added the 'resources-are-not-supported' value for use with the "job-state-reasons" Job Description
1848 attribute to indicate that a user has supplied a custom name.
 - 1849 23. Clarified that if a Printer supports "job-sheets-col", it MUST also support the IPP/1.1 "job-sheets" Job
1850 Template attribute.
 - 1851 24. Clarified that if a Printer supports "media-col", it MUST also support the IPP/1.1 "media" Job
1852 Template attribute.
 - 1853 25. Clarified that if a Printer supports "media-col-ready", it MUST also support the IPP/1.1 "media-
1854 ready" Printer attribute.
 - 1855 26. Changed the attribute syntax for "job-account-id-supported", "job-message-to-operator-supported",
1856 "job-recipient-name-supported", and "job-sheet-message-supported" from 'boolean' to 'integer(1:255)'
1857 to indicate the maximum string length supported, since IPP is often a gateway to another system that
1858 can't store the string length required for conforming IPP Printers.
 - 1859 27. Added notes about the conversion between English and metric for different types of media.

1860

1861

13.5 Changes to the January 30, 2000 to create the February 7, 2000 version

1863

The following changes were made to the January 30, 2000 version to create the February 7, 2000 version:

1865

- 1866 1. Changed the attribute syntax of "cover-front-supported" and "cover-back-supported" from 'collection' to
1867 'boolean', since a Printer MUST support all (both) member attributes and any combinations of values.
- 1868 2. Changed the 'sheet' member attribute in each of the following collections to give them distinct names so
1869 that the "xxx-supported" Printer attribute can indicate their respective (potentially different) values:
1870 "job-accounting-sheets", "job-error-sheets", "job-sheets", and "separator-sheets".
- 1871 3. Added "media-" to the beginning of each member attribute of the "media" collection, so that ordinary
1872 "media-xxx-supported" could be used to represent their individual supported values.
- 1873 4. Removed the 'name(MAX)' choice from the "media-size" member attribute. If the properties of a
1874 medium are being given, either the keyword name or the exact numerical dimensions known to the
1875 implementation, not a name made up by the administrator.
- 1876 5. Added "media-size-supported (1setOf collection) which contains the combinations of numerical sizes
1877 supported (x-dimension and y-dimension) by the Printer. This "xxx-supported" attribute is the only one
1878 that has a value of '1setOf collection' in order to list the pairs of x and y dimensions supported. The
1879 attribute syntax of the "x-dimension" and "y-dimension" is a choice of 'integer(0:MAX)' or
1880 'rangeOfInteger(0:MAX)' to cover the case of continuous media and cut sheet printers that can cut the
1881 medium to any size within the specified range.
- 1882 6. Changed the "media-supported" from containing a collection whose member attributes listed the
1883 supported values that the client could supply as member attributes to just containing a new out-of-band
1884 'any-collection' value that indicates that the implementation allows any combination of member
1885 attributes that are indicated by the corresponding "xxx-supported" Printer attributes.

1886

13.6 Changes to the January 28, 2000 to create the January 30, 2000 version

1888

The following changes were made to the January 28, 2000 version to create the January 30, 2000 version:

1890

- 1891 1. Ordered the Job Template attributes alphabetically.
- 1892 2. Add 'name(MAX)' to Job Template attributes that had (type3 keyword | collection) to be consistent with
1893 IPP/1.1 that has (type3 keyword | name(MAX)).

1894

13.7 Changes to create the January 28, 2000 version

1896

Initial version.

1898

1899

14 Appendix B: Possible future additions

1901

This appendix lists possible future additions.

1903

1904
1905
1906
1907
1908
1909
1910

14.1 Possible future keyword additions for "media" and "media-col" attributes

These are additional standard keyword values which are used by the implementation as a simple method for media selection. When combinations of these values are needed for media selection, it is RECOMMENDED that the attribute "media-col" collection be used to prevent proliferation of complex keywords and names.

'plain'	The plain media as specified by the output device.
'pre-punched'	The pre-punched media as specified by the output device.
'transparency'	The transparent media as specified by the output device.
'letterhead'	The pre-printed letterhead media as specified by the output device.
'heavyweight'	The heavyweight media as specified by the output device.
'recycled'	The recycled media as specified by the output device.
'bond'	The bonded media as specified by the output device.
'labels'	The labels media as specified by the output device.
'pre-printed'	The pre-printed media as specified by the output device.
'custom1'	Custom value 1 defined for the site
'custom2'	Custom value 2 defined for the site
'custom3'	Custom value 3 defined for the site
'custom4'	Custom value 4 defined for the site
'custom5'	Custom value 5 defined for the site
'custom6'	Custom value 6 defined for the site
'custom7'	Custom value 7 defined for the site

1911
1912
1913
1914
1915
1916
1917
1918
1919
1920

14.2 Possible future additions to the "media-col" Job Template attribute

Since there would be some redundancy between the above proposed keywords for "media" and "media-col" and other "media-col" member attributes, provide some way to indicate which member attributes subsume which keyword values, depending on which member attributes are supported. Then a Printer can indicate which keyword values map to which member attributes. The following table shows what these redundancies would be:

"media-description" keyword values	redundant member attributes
------------------------------------	-----------------------------

'plain', 'bond', 'transparency'	"media-opacity" - 'opaque', 'transparent' values
'pre-punched'	"media-hole-count" - non-zero value
'plain'	"media-pre-printer" - 'blank' value
'letterhead'	"media-pre-printed" - 'letterhead' value
'pre-printed'	"media-pre-printed" - 'pre-printed' value
'heavyweight'	"media-weight-metric", "media-weight-english"
'recycled'	"media-recycled" - 'standard' value
'labels'	"media-label-type" - 'standard' value

1921
1922
1923
1924
1925
1926
1927
1928
1929
1930

Should we add a new member attribute, called "media-kind" (type3 keyword | name) with value like: labels, envelope, envelope-plain, envelope-window, continuous-long, continuous-short, multi-layer, and multi-part-form from the Printer MIB?

Should the values: 'bond', 'Index-Bristol-tab-stock', 'cover-stock', 'rank-paper' and 'newsprint' (see "media-weight" member attribute description) be added to this new "media-kind" member attribute?

1931
1932
1933

15 Appendix C: Description of the IEEE Industry Standards and Technology (ISTO)

1934
1935
1936
1937
1938
1939

The IEEE-ISTO is a not-for-profit corporation offering industry groups an innovative and flexible operational forum and support services. The IEEE-ISTO provides a forum not only to develop standards, but also to facilitate activities that support the implementation and acceptance of standards in the marketplace. The organization is affiliated with the IEEE (<http://www.ieee.org/>) and the IEEE Standards Association (<http://standards.ieee.org/>).

1940
1941

For additional information regarding the IEEE-ISTO and its industry programs visit:

<http://www.ieee-isto.org>.

1943

1944
1945

16 Appendix D: Description of the IEEE-ISTO PWG

1946
1947
1948
1949
1950
1951
1952
1953
1954
1955

The Printer Working Group (or PWG) is a Program of the IEEE Industry Standards and Technology Organization (ISTO) with member organizations including printer manufacturers, print server developers, operating system providers, network operating systems providers, network connectivity vendors, and print management application developers. The group is chartered to make printers and the applications and operating systems supporting them work together better. All references to the PWG in this document implicitly mean "The Printer Working Group, a Program of the IEEE ISTO." In order to meet this objective, the PWG will document the results of their work as open standards that define print related protocols, interfaces, procedures and conventions. Printer manufacturers and vendors of printer related software will benefit from the interoperability provided by voluntary conformance to these standards.

1956 In general, a PWG standard is a specification that is stable, well understood, and is technically competent,
1957 has multiple, independent and interoperable implementations with substantial operational experience, and
1958 enjoys significant public support.

1959
1960 For additional information regarding the Printer Working Group visit:

1961
1962 <http://www.pwg.org>
1963
1964
1965

1966 **17 Appendix E: IEEE Industry Standards and Technology Organization** 1967 **Copyright Statement**

1968
1969 Copyright (C) 2000, IEEE Industry Standards and Technology Organization. All rights reserved.
1970

1971 This document may be copied and furnished to others, and derivative works that comment on, or otherwise
1972 explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in
1973 part, without restriction of any kind, provided that the above copyright notice, this paragraph and the title of
1974 the Document as referenced below are included on all such copies and derivative works. However, this
1975 document itself may not be modified in any way, such as by removing the copyright notice or references to
1976 the IEEE-ISTO and the Printer Working Group, a program of the IEEE-ISTO.
1977

1978 Title: Internet Printing Protocol: Production Printing Attributes - Set1
1979

1980 The IEEE-ISTO and the Printer Working Group DISCLAIM ANY AND ALL WARRANTIES,
1981 WHETHER EXPRESS OR IMPLIED INCLUDING (WITHOUT LIMITATION) ANY IMPLIED
1982 WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
1983

1984 The Printer Working Group, a program of the IEEE-ISTO, reserves the right to make changes to the
1985 document without further notice. The document may be updated, replaced or made obsolete by other
1986 documents at any time.
1987

1988 The IEEE-ISTO takes no position regarding the validity or scope of any intellectual property or other rights
1989 that might be claimed to pertain to the implementation or use of the technology described in this document
1990 or the extent to which any license under such rights might or might not be available; neither does it
1991 represent that it has made any effort to identify any such rights.
1992

1993 The IEEE-ISTO invites any interested party to bring to its attention any copyrights, patents, or patent
1994 applications, or other proprietary rights which may cover technology that may be required to implement the
1995 contents of this document. The IEEE-ISTO and its programs shall not be responsible for identifying patents
1996 for which a license may be required by a document and/or IEEE-ISTO Industry Group Standard or for
1997 conducting inquiries into the legal validity or scope of those patents that are brought to its attention.
1998 Inquiries may be submitted to the IEEE-ISTO by e-mail at:

2000 ieee-isto@ieee.org.

2001

2002 The Printer Working Group acknowledges that the IEEE-ISTO (acting itself or through its designees) is,
2003 and shall at all times, be the sole entity that may authorize the use of certification marks, trademarks, or
2004 other special designations to indicate compliance with these materials.

2005

2006 Use of this document is wholly voluntary. The existence of this document does not imply that there are no
2007 other ways to produce, test, measure, purchase, market, or provide other goods and services related to its
2008 scope.

2009