

IDS HCD attributes for standardized PWG remediation

Proposal: PWG defines a standardized generic remediation process for the HCD attributes indicated below. Remediation of any other attributes would require a vendor supplied remediation process.

HCD_Default_Password_Enabled	Could be remediated by providing new password value as part of remediation. Requires manual intervention.
HCD_Firewall_Setting	Would require that PWG standardize the firewall values. Applies to the interface being assessed if supported. Should this be a global setting only?
HCD_Forwarding_Enabled	Can be set on/off. The device would be responsible to make sure the correct actions were performed. Setting applies to all external interfaces.
HCD_PSTN_Fax_Enabled	Can be set on/off. The device would be responsible to make sure the correct actions were performed.
HCD_Time_Source	Device must support URIs for time source, or standardized string (“onboard”) for internal clock
HCD_User_Application_Enabled	Can be set on/off
HCD_User_Application_Persistence_Enabled	Can be set on/off
HCD_Firmware_*	Look into semantic model or provide a URL?
HCD_Certification_State	Provide URL or manual intervention?
HCD_Configuration_State	Provide URL or manual intervention?
HCD_Vendor_SMI_Code	Indicate Fatal error
HCD_Vendor_Name	Indicate Fatal error
HCD_Machine_Type_Model	Indicate Fatal error